Classified according to WHMIS 2015

## **SECTION 1: Identification**

#### 1.1. Product Identifier

**Trade Name or Designation:** Spiking Solution for Water and Soil - CLP

Product Number: RSPIKE1

Other Identifying Product Numbers: RSPIKE1-100

#### 1.2. Recommended Use and Restrictions on Use

General Laboratory Reagent

#### 1.3. Details of the Supplier of the Safety Data Sheet

Company: Ricca Chemical Company Address: 448 West Fork Drive

Arlington, TX 76012 USA

**Telephone:** 888-467-4222

#### 1.4. Emergency Telephone Number (24 hours)

CHEMTREC (USA) 800-424-9300 CHEMTREC (International) 1+ 703-527-3887

Product Number: RSPIKE1 Page 1 of 35



## **Safety Data Sheet**

## SECTION 2: Hazard(s) Identification

#### 2.1. Classification of the Substance or Mixture

For the full text of the Hazard and Precautionary Statements listed below, see Section 16.

| Hazard Class                                   | Category   | Hazard<br>Statements | Precautionary Statements:                |
|--|------------|----------------------|--|
|  | Cutogory   | Otatomonto           | <u> </u>                                 |
| Acute Toxicity - Inhalation                    | Category 2 | H330                 | P260, P271, P285, P304+P340, P310, P320, |
|  |            |                      | P403+P233, P405, P501                    |
| Skin Corrosion / Irritation                    | Category 1 | H314                 | P260, P264, P280, P301+P330+P331,        |
|  |            |                      | P303+P361+P353, P363, P304+P340, P310,   |
|  |            |                      | P321, P305+P351+P338, P405, P501         |
| Eye Damage / Irritation                        | Category 1 | H318                 | P280, P305+P351+P338, P310               |
| Corrosive to Metals                            | Category 1 | H290                 | P234, P390, P406                         |
| Hazardous to the Aquatic Environment (Acute)   | Category 2 | H401                 | P273, P501                               |
| Hazardous to the Aquatic Environment (Chronic) | Category 2 | H411                 | P273, P391, P501                         |

### 2.2. GHS Label Elements

#### Pictograms:







Signal Word: Danger

#### **Hazard Statements:**

| <b>Hazard Number</b> | Hazard Statement                                 |
|----------------------|--|
| H290                 | May be corrosive to metals.                      |
| H314                 | Causes severe skin burns and eye damage.         |
| H318                 | Causes serious eye damage.                       |
| H330                 | Fatal if inhaled.                                |
| H401                 | Toxic to aquatic life.                           |
| H411                 | Toxic to aquatic life with long lasting effects. |

Product Number: RSPIKE1 Page 2 of 35

#### **Precautionary Statements:**

| Precautionary Number | Precautionary Statement  |
|----------------------|--|
| P234                 | Keep only in original container.   |
| P260                 | Do not breathe fumes, mist, vapors, or spray.  |
| P264                 | Wash arms, hands and face thoroughly after handling.   |
| P271                 | Use only outdoors or in a well-ventilated area.  |
| P273                 | Avoid release to the environment.  |
| P280                 | Wear protective gloves and eye protection.   |
| P285                 | In case of inadequate ventilation wear respiratory protection.                                     |
| P301+P330+P331       | IF SWALLOWED: rinse mouth. Do NOT induce vomiting.   |
| P303+P361+P353       | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.       |
| P304+P340            | IF INHALED: Remove person to fresh air and keep comfortable for breathing.                         |
| P305+P351+P338       | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and |
|                      | easy to do. Continue rinsing.  |
| P310                 | Immediately call a POISON CENTER or physician.   |
| P320                 | Specific treatment is urgent (Wash areas of contact with water.).                                  |
| P321                 | Specific treatment (Wash areas of contact with water.).  |
| P363                 | Wash contaminated clothing before reuse.   |
| P390                 | Absorb spillage to prevent material damage.  |
| P391                 | Collect spillage.  |
| P403+P233            | Store in a well-ventilated place. Keep container tightly closed.                                   |
| P405                 | Store locked up.   |
| P406                 | Store in corrosive resistant container with a resistant inner liner.                               |
| P501                 | Dispose of contents in accordance with local, state, federal and international regulations.        |

### 2.4. Hazards not Otherwise Classified or Covered by GHS

Data not available.

Product Number: RSPIKE1 Page 3 of 35



## **Safety Data Sheet**

### **SECTION 3: Composition / Information on Ingredients**

### 3.1. Components of Substance or Mixture

| Chemical Name                | Formula                           | Molecular Weight | <b>CAS Number</b> | Weight% |
|------------------------------|-----------------------------------|------------------|-------------------|---------|
| Water                        | H <sub>2</sub> O                  | 18.01 g/mol      | 7732-18-5         | 94.74   |
| Nitric Acid                  | HNO <sub>3</sub>                  | 63.01 g/mol      | 7697-37-2         | 4.83    |
| Aluminum Nitrate Nonahydrate | $AI(NO_3)_3 \cdot 9H_2O$          | 375.13 g/mol     | 7784-27-2         | 0.27    |
| Barium Nitrate               | Ba(NO <sub>3</sub> ) <sub>2</sub> | 261.33 g/mol     | 10022-31-8        | < 0.1   |
| Selenium                     | Se                                | 78.95 g/mol      | 7782-49-2         | < 0.1   |
| Arsenic                      | As                                | 74.92 g/mol      | 7440-38-2         | < 0.1   |
| Thallium                     | TI                                | 204.38 g/mol     | 7440-28-0         | < 0.1   |
| Chromium Nitrate Nonahydrate | $Cr(NO_3)_3 \cdot 9H_2O$          | 238.01 g/mol     | 7789-02-8         | < 0.1   |
| Iron                         | Fe                                | 55.84 g/mol      | 7439-89-6         | < 0.1   |
| Antimony Trioxide            | $Sb_2O_3$                         | 291.51 g/mol     | 1309-64-4         | < 0.1   |
| Zinc                         | Zn                                | 65.40 g/mol      | 7440-66-6         | < 0.1   |
| Vanadium                     | V                                 | 50.94 g/mol      | 7440-62-2         | < 0.1   |
| Cobalt                       | Со                                | 58.93 g/mol      | 7440-48-4         | < 0.1   |
| Nickel                       | Ni                                | 58.69 g/mol      | 7440-02-0         | < 0.1   |
| Manganese                    | Mn                                | 54.93 g/mol      | 7439-96-5         | < 0.1   |
| Lead                         | Pb                                | 207.2 g/mol      | 7439-92-1         | < 0.1   |
| Copper                       | Cu                                | 63.54 g/mol      | 7440-50-8         | < 0.1   |
| Hydrofluoric Acid            | HF                                | 20.00 g/mol      | 7664-39-3         | < 0.1   |
| Cadmium                      | Cd                                | 112.41 g/mol     | 7440-43-9         | < 0.1   |
| Beryllium                    | Be                                | 9.01 g/mol       | 7440-41-7         | < 0.1   |
| Silver                       | Ag                                | 107.86 g/mol     | 7440-22-4         | < 0.1   |

### **SECTION 4: First-Aid Measures**

#### 4.1. General First Aid Information

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. May cause irritation, redness, pain, and tearing.

**Inhalation:** IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin Contact: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. May cause irritation, redness

and pain. Contact will discolor skin yellow-brown depending on exposure which will wear off after a period of time.

Product Number: RSPIKE1 Page 4 of 35



Ingestion: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Dilute with water or milk. Do not induce vomiting. Call a

physician if necessary.

#### 4.2. Most Important Symptoms and Effects, Acute and Delayed

Causes severe skin burns and eye damage. Causes serious eye damage. Fatal if inhaled. Contains low levels of known and suspected carcinogens. Corrosive Liquid. May be fatal if swallowed. Avoid contact with skin, eyes, and clothing. Avoid breathing vapor. If swallowed, do not induce vomiting. Dilute with water and call a physician. Wash areas of contact with plenty of water. Potential symptoms of overexposure are irritation of the eyes, mucous membranes and skin, dental erosion, bronchitis, pneumonitis, delayed pulmonary edema. EYE CONTACT: May cause irritation, redness, pain, and tearing. SKIN CONTACT: May cause irritation, redness and pain. Contact will discolor skin yellow-brown depending on exposure which will wear off after a period of time.

#### 4.3. Medical Attention or Special Treatment Needed

Immediately call a POISON CENTER or physician. Specific treatment is urgent (Wash areas of contact with water.). Specific treatment (Wash areas of contact with water.). Irrigate immediately with large quantity of water for at least 15 minutes. Call a physician if irritation develops. Remove to fresh air. Give artificial respiration if necessary. If breathing is difficult, give oxygen. Immediately flush with plenty of water for at least 15 minutes. Remove any contaminated clothing. Wash with soap and water, then flush again with water. Call a physician if irritation develops. Dilute with water or milk. Do not induce vomiting. Call a physician if necessary.

### **SECTION 5: Fire-Fighting Measures**

#### 5.1. Extinguishing Media

Use water or water spray.

### 5.2. Specific Hazards Arising from the Substance or Mixture

Not combustible, but substance is an oxidizer and its heat of reaction with reducing agents or combustibles may cause ignition. Can react with metals to release flammable hydrogen gas.

### 5.3. Special Protective Equipment for Firefighters

Use protective clothing and breathing equipment appropriate for the surrounding fire.

#### **SECTION 6: Accidental Release Measures**

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Wear protective gloves and eye protection. In case of inadequate ventilation wear respiratory protection.

### 6.2. Cleanup and Containment Methods and Materials

Do not flush to sewer. Absorb with suitable material. Containerize for disposal with a hazardous waste disposal facility. Dispose of in accordance with local regulations.

Product Number: RSPIKE1 Page 5 of 35

## **SECTION 7: Handling and Storage**

#### 7.1. Precautions for Safe Handling and Storage Conditions

Store in corrosive resistant container with a resistant inner liner. As with all chemicals, wash hands thoroughly after handling. Avoid contact with eyes and skin. Protect from freezing and physical damage.

Product Number: RSPIKE1 Page 6 of 35



## **Safety Data Sheet**

## **SECTION 8: Exposure Controls / Personal Protection**

#### **8.1 Control Parameters**

| Chemical Name                 | Limit Type | Country | Exposure Limit   | Information Source   |
|-------------------------------|------------|---------|--|--|
| Barium Nitrate (10022-31-8)   | TLV-TWA    | USA     | "0.5 mg/m³ TWA (as Ba)" As Barium soluble compounds [RR-00049-7]                                 | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Barium Nitrate (10022-31-8)   | TWA        | USA     | "0.5 mg/m³ TWA (regulated under CAS 7440-39-3, as Ba)" As Barium, soluble compounds [RR-00049-7] | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs)             |
| Barium Nitrate (10022-31-8)   | TLV-TWA    | USA     | 0.5 mg/m³ TWA (as Ba)  | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Barium Nitrate (10022-31-8)   | TWA        | USA     | 0.5 mg/m³ TWA (regulated under CAS 7440-39-3, as Ba)   | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs)             |
| Antimony Trioxide (1309-64-4) | TWA        | USA     | "0.5 mg/m³ TWA (as Sb)" As Antimony compounds [RR-00585-6]                                       | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs)             |
| Antimony Trioxide (1309-64-4) | TLV-TWA    | USA     | 0.02 mg/m³ TWA (inhalable particulate matter)  | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Antimony Trioxide (1309-64-4) | TWA        | USA     | "0.5 mg/m³ TWA (as Sb)" As Antimony compounds [RR-00585-6]                                       | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs)             |
| Antimony Trioxide (1309-64-4) | TLV-TWA    | USA     | "0.5 mg/m³ TWA (as Sb)" As Antimony compounds [RR-00585-6]                                       | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Antimony Trioxide (1309-64-4) | TWA        | USA     | "0.5 mg/m³ TWA (as Sb)" As Antimony compounds [RR-00585-6]                                       | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs)             |
| Antimony Trioxide (1309-64-4) | TLV-TWA    | USA     | "0.5 mg/m³ TWA (as Sb)" As Antimony compounds [RR-00585-6]                                       | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Antimony Trioxide (1309-64-4) | TLV-TWA    | USA     | "0.5 mg/m³ TWA (as Sb)"<br>As Antimony compounds<br>[RR-00585-6]                                 | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Antimony Trioxide (1309-64-4) | TWA        | USA     | "0.5 mg/m³ TWA (as Sb)" As Antimony compounds [RR-00585-6]                                       | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs)             |

Product Number: RSPIKE1 Page 7 of 35



# **Safety Data Sheet**

| Antimony Trioxide (1309-64-4) | TWA            | USA  | 0.5 mg/m³ TWA (as Sb)              | U.S OSHA - Final PELs - Time          |
|-------------------------------|----------------|------|------------------------------------|---------------------------------------|
|                               | T1 1 / T14 / A |      | 0.5 ( 0.7144 ( 01)                 | Weighted Averages (TWAs)              |
| Antimony Trioxide (1309-64-4) | TLV-TWA        | USA  | 0.5 mg/m³ TWA (as Sb)              | ACGIH - Threshold Limit Values - Time |
| A :: T: :1 (1000 04 4)        | T14/4          | 1104 | 10.5 / 0.TMA / OLVI                | Weighted Averages (TLV-TWA)           |
| Antimony Trioxide (1309-64-4) | TWA            | USA  | "0.5 mg/m³ TWA (as Sb)"            | U.S OSHA - Final PELs - Time          |
|                               |                |      | As Antimony compounds [RR-00585-6] | Weighted Averages (TWAs)              |
| Antimony Trioxide (1309-64-4) | TLV-TWA        | USA  | "0.5 mg/m³ TWA (as Sb)"            | ACGIH - Threshold Limit Values - Time |
|                               |                |      | As Antimony compounds              | Weighted Averages (TLV-TWA)           |
|                               |                |      | [RR-00585-6]                       |                                       |
| Lead (7439-92-1)              | PEL            | USA  | 30 μg/m³ Action Level (See         | U.S OSHA - Specifically Regulated     |
| ,                             |                |      | 29 CFR 1910.1025); 50              | Chemicals with PELs                   |
|                               |                |      | μg/m³ TWA                          |                                       |
| Lead (7439-92-1)              | TLV-TWA        | USA  | 0.05 mg/m³ TWA                     | ACGIH - Threshold Limit Values - Time |
|                               |                |      | -                                  | Weighted Averages (TLV-TWA)           |
| Lead (7439-92-1)              | TWA            | USA  | 50 μg/m³ TWA                       | U.S OSHA - Final PELs - Time          |
|                               |                |      |                                    | Weighted Averages (TWAs)              |
| Manganese (7439-96-5)         | PEL-Ceiling    | USA  | "5 mg/m3 Ceiling (as Mn)"          | U.S OSHA - Final PELs - Ceiling       |
|                               |                |      | As Manganese compounds             | Limits                                |
|                               |                |      | [RR-00602-0]                       |                                       |
| Manganese (7439-96-5)         | PEL-Ceiling    | USA  | "5 mg/m3 Ceiling (as Mn)"          | U.S OSHA - Final PELs - Ceiling       |
|                               |                |      | As Manganese compounds             | Limits                                |
|                               |                |      | [RR-00602-0]                       |                                       |
| Manganese (7439-96-5)         | PEL-Ceiling    | USA  | "5 mg/m3 Ceiling (as Mn)"          | U.S OSHA - Final PELs - Ceiling       |
|                               |                |      | As Manganese compounds             | Limits                                |
|                               |                |      | [RR-00602-0]                       |                                       |
| Manganese (7439-96-5)         | PEL-Ceiling    | USA  | "5 mg/m3 Ceiling (as Mn)"          | U.S OSHA - Final PELs - Ceiling       |
|                               | _              |      | As Manganese compounds             | Limits                                |
|                               |                |      | [RR-00602-0]                       |                                       |
| Manganese (7439-96-5)         | PEL-Ceiling    | USA  | "5 mg/m³ Ceiling (as Mn)"          | U.S OSHA - Final PELs - Ceiling       |
|                               |                |      | As Manganese compounds             | Limits                                |
|                               |                |      | [RR-00602-0]                       |                                       |
| Manganese (7439-96-5)         | TLV-TWA        | USA  | 0.02 mg/m³ TWA                     | ACGIH - Threshold Limit Values - Time |
|                               |                |      | (respirable particulate            | Weighted Averages (TLV-TWA)           |
|                               |                |      | matter); 0.1 mg/m <sup>3</sup> TWA | - · · · · · ·                         |
|                               |                |      | (inhalable particulate             |                                       |
|                               |                |      | matter)                            |                                       |
| Manganese (7439-96-5)         | PEL-Ceiling    | USA  | 5 mg/m³ Ceiling (fume)             | U.S OSHA - Final PELs - Ceiling       |
| ,                             | J              |      | 3 3 , ,                            | Limits                                |

Product Number: RSPIKE1 Page 8 of 35



# **Safety Data Sheet**

| Manganese (7439-96-5) | PEL-Ceiling | USA | "5 mg/m³ Ceiling (as Mn)"<br>As Manganese compounds | U.S OSHA - Final PELs - Ceiling<br>Limits |
|-----------------------|-------------|-----|---|---|
|                       |             |     | [RR-00602-0]  | Liffits                                   |
| Manganese (7439-96-5) | TLV-TWA     | USA | 0.02 mg/m³ TWA                                      | ACGIH - Threshold Limit Values - Time     |
|                       |             |     | (respirable particulate                             | Weighted Averages (TLV-TWA)               |
|                       |             |     | matter, as Mn); 0.1 mg/m <sup>3</sup>               |   |
|                       |             |     | TWA (inhalable particulate                          |   |
|                       |             |     | matter, as Mn)                                      |   |
| Nickel (7440-02-0)    | TLV-TWA     | USA | 1.5 mg/m³ TWA (inhalable                            | ACGIH - Threshold Limit Values - Time     |
|                       |             |     | particulate matter)                                 | Weighted Averages (TLV-TWA)               |
| Nickel (7440-02-0)    | TWA         | USA | 1 mg/m³ TWA   | U.S OSHA - Final PELs - Time              |
|                       |             |     |   | Weighted Averages (TWAs)                  |
| Silver (7440-22-4)    | TLV-TWA     | USA | 0.1 mg/m³ TWA (dust and                             | ACGIH - Threshold Limit Values - Time     |
|                       |             |     | fume)   | Weighted Averages (TLV-TWA)               |
| Silver (7440-22-4)    | TWA         | USA | 0.01 mg/m³ TWA                                      | U.S OSHA - Final PELs - Time              |
|                       |             |     |   | Weighted Averages (TWAs)                  |
| Thallium (7440-28-0)  | TLV-TWA     | USA | "0.02 mg/m³ TWA                                     | ACGIH - Threshold Limit Values - Time     |
|                       |             |     | (inhalable particulate                              | Weighted Averages (TLV-TWA)               |
|                       |             |     | matter, as TI)" As Thallium                         |   |
|                       |             |     | compounds [RR-00575-4]                              |   |
| Thallium (7440-28-0)  | TLV-TWA     | USA | "0.02 mg/m³ TWA                                     | ACGIH - Threshold Limit Values - Time     |
|                       |             |     | (inhalable particulate                              | Weighted Averages (TLV-TWA)               |
|                       |             |     | matter, as TI)" As Thallium                         |   |
|                       |             |     | compounds [RR-00575-4]                              |   |
| Thallium (7440-28-0)  | TLV-TWA     | USA | "0.02 mg/m <sup>3</sup> TWA                         | ACGIH - Threshold Limit Values - Time     |
|                       |             |     | (inhalable particulate                              | Weighted Averages (TLV-TWA)               |
|                       |             |     | matter, as TI)" As Thallium                         |   |
|                       |             |     | compounds [RR-00575-4]                              |   |
| Thallium (7440-28-0)  | TLV-TWA     | USA | "0.02 mg/m³ TWA                                     | ACGIH - Threshold Limit Values - Time     |
|                       |             |     | (inhalable particulate                              | Weighted Averages (TLV-TWA)               |
|                       |             |     | matter, as TI)" As Thallium                         |   |
|                       |             |     | compounds [RR-00575-4]                              |   |
| Thallium (7440-28-0)  | TLV-TWA     | USA | "0.02 mg/m <sup>3</sup> TWA                         | ACGIH - Threshold Limit Values - Time     |
|                       |             |     | (inhalable particulate                              | Weighted Averages (TLV-TWA)               |
|                       |             |     | matter, as TI)" As Thallium                         |   |
|                       |             |     | compounds [RR-00575-4]                              |   |
| Thallium (7440-28-0)  | TLV-TWA     | USA | "0.02 mg/m³ TWA                                     | ACGIH - Threshold Limit Values - Time     |
|                       |             |     | (inhalable particulate                              | Weighted Averages (TLV-TWA)               |
|                       |             |     | matter, as TI)" As Thallium                         |   |
|                       |             |     | compounds [RR-00575-4]                              |   |

Product Number: RSPIKE1 Page 9 of 35



# **Safety Data Sheet**

| Thallium (7440-28-0)    | TLV-TWA      | USA  | "0.02 mg/m³ TWA                           | ACGIH - Threshold Limit Values - Time    |
|-------------------------|--------------|------|---|--|
| 111a111u111 (1440-20-0) | ILV-IVVA     | USA  | (inhalable particulate                    | Weighted Averages (TLV-TWA)              |
|                         |              |      | matter, as TI)" As Thallium               | Weighted Averages (TEV-TWA)              |
|                         |              |      | compounds [RR-00575-4]                    |  |
| Thallium (7440-28-0)    | TLV-TWA      | USA  | "0.02 mg/m³ TWA                           | ACGIH - Threshold Limit Values - Time    |
| 111aiiiui11 (7440-20-0) | ILV-IVVA     | UUA  | (inhalable particulate                    | Weighted Averages (TLV-TWA)              |
|                         |              |      | matter, as TI)" As Thallium               | Weighted Averages (TEV-TWA)              |
|                         |              |      | compounds [RR-00575-4]                    |  |
| Thallium (7440-28-0)    | TLV-TWA      | USA  | "0.02 mg/m³ TWA                           | ACGIH - Threshold Limit Values - Time    |
| 111a111u111 (1440-20-0) | ILV-IVVA     | USA  | (inhalable particulate                    |  |
|                         |              |      | matter, as TI)" As Thallium               | Weighted Averages (TLV-TWA)              |
|                         |              |      |   |  |
| Thallium (7440-28-0)    | TLV-TWA      | USA  | compounds [RR-00575-4]<br>"0.02 mg/m³ TWA | ACGIH - Threshold Limit Values - Time    |
| 111ailiui11 (7440-26-0) | ILV-IVVA     | USA  | _   |  |
|                         |              |      | (inhalable particulate                    | Weighted Averages (TLV-TWA)              |
|                         |              |      | matter, as TI)" As Thallium               |  |
| The III (7440.00.0)     | T1 \ / T\A/A | 1104 | compounds [RR-00575-4]                    | ACOULT Through a bill for 1777 and Trans |
| Thallium (7440-28-0)    | TLV-TWA      | USA  | "0.02 mg/m³ TWA                           | ACGIH - Threshold Limit Values - Time    |
|                         |              |      | (inhalable particulate                    | Weighted Averages (TLV-TWA)              |
|                         |              |      | matter, as TI)" As Thallium               |  |
| TI III (7440.00.0)      | T1 1/ T14/A  | 1104 | compounds [RR-00575-4]                    | A000 T                                   |
| Thallium (7440-28-0)    | TLV-TWA      | USA  | 0.02 mg/m³ TWA (inhalable                 | ACGIH - Threshold Limit Values - Time    |
| <b>-</b> : (            |              |      | particulate matter)                       | Weighted Averages (TLV-TWA)              |
| Thallium (7440-28-0)    | TLV-TWA      | USA  | "0.02 mg/m³ TWA                           | ACGIH - Threshold Limit Values - Time    |
|                         |              |      | (inhalable particulate                    | Weighted Averages (TLV-TWA)              |
|                         |              |      | matter, as TI)" As Thallium               |  |
| /=                      |              |      | compounds [RR-00575-4]                    |  |
| Arsenic (7440-38-2)     | TWA          | USA  | "10 μg/m³ TWA (as As)" As                 | U.S OSHA - Final PELs - Time             |
|                         |              |      | Arsenic, inorganic                        | Weighted Averages (TWAs)                 |
|                         |              |      | compounds [RR-00065-7]                    |  |
| Arsenic (7440-38-2)     | TLV-TWA      | USA  | "0.01 mg/m <sup>3</sup> TWA (as As)"      | ACGIH - Threshold Limit Values - Time    |
|                         |              |      | As Arsenic inorganic                      | Weighted Averages (TLV-TWA)              |
|                         |              |      | compounds [RR-00065-7]                    |  |
| Arsenic (7440-38-2)     | PEL          | USA  | "10 μg/m³ TWA (See 29                     | U.S OSHA - Specifically Regulated        |
|                         |              |      | CFR 1910.1018; except                     | Chemicals with PELs                      |
|                         |              |      | Arsine, as As); 5 µg/m <sup>3</sup>       |  |
|                         |              |      | Action Level (as As)" As                  |  |
|                         |              |      | Inorganic arsenic                         |  |
|                         |              |      | compounds [RR-00065-7]                    |  |

Product Number: RSPIKE1 Page 10 of 35



# **Safety Data Sheet**

| Arsenic (7440-38-2) | PEL     | USA | "10 μg/m³ TWA (See 29               | U.S OSHA - Specifically Regulated     |
|---------------------|---------|-----|-------------------------------------|---------------------------------------|
|                     |         |     | CFR 1910.1018; except               | Chemicals with PELs                   |
|                     |         |     | Arsine, as As); 5 μg/m <sup>3</sup> |                                       |
|                     |         |     | Action Level (as As)" As            |                                       |
|                     |         |     | Inorganic arsenic                   |                                       |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TWA     | USA | "10 μg/m³ TWA (as As)" As           | U.S OSHA - Final PELs - Time          |
|                     |         |     | Arsenic, inorganic                  | Weighted Averages (TWAs)              |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TLV-TWA | USA | "0.01 mg/m3 TWA (as As)"            | ACGIH - Threshold Limit Values - Time |
|                     |         |     | As Arsenic inorganic                | Weighted Averages (TLV-TWA)           |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TWA     | USA | "10 μg/m³ TWA (as As)" As           | U.S OSHA - Final PELs - Time          |
|                     |         |     | Arsenic, inorganic                  | Weighted Averages (TWAs)              |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TLV-TWA | USA | "0.01 mg/m3 TWA (as As)"            | ACGIH - Threshold Limit Values - Time |
| ,                   |         |     | As Arsenic inorganic                | Weighted Averages (TLV-TWA)           |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | PEL     | USA | "10 μg/m³ TWA (See 29               | U.S OSHA - Specifically Regulated     |
|                     |         |     | CFR 1910.1018; except               | Chemicals with PELs                   |
|                     |         |     | Arsine, as As); 5 μg/m <sup>3</sup> |                                       |
|                     |         |     | Action Level (as As)" As            |                                       |
|                     |         |     | Inorganic arsenic                   |                                       |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | PEL     | USA | "10 μg/m³ TWA (See 29               | U.S OSHA - Specifically Regulated     |
|                     |         |     | CFR 1910.1018; except               | Chemicals with PELs                   |
|                     |         |     | Arsine, as As); 5 μg/m <sup>3</sup> |                                       |
|                     |         |     | Action Level (as As)" As            |                                       |
|                     |         |     | Inorganic arsenic                   |                                       |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TLV-TWA | USA | "0.01 mg/m3 TWA (as As)"            | ACGIH - Threshold Limit Values - Time |
|                     |         |     | As Arsenic inorganic                | Weighted Averages (TLV-TWA)           |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TWA     | USA | "10 μg/m³ TWA (as As)" As           | U.S OSHA - Final PELs - Time          |
|                     |         |     | Arsenic, inorganic                  | Weighted Averages (TWAs)              |
|                     |         |     | compounds [RR-00065-7]              | - ,                                   |

Product Number: RSPIKE1 Page 11 of 35



# **Safety Data Sheet**

| Arsenic (7440-38-2) | PEL     | USA | "10 μg/m³ TWA (See 29               | U.S OSHA - Specifically Regulated     |
|---------------------|---------|-----|-------------------------------------|---------------------------------------|
|                     |         |     | CFR 1910.1018; except               | Chemicals with PELs                   |
|                     |         |     | Arsine, as As); 5 μg/m <sup>3</sup> |                                       |
|                     |         |     | Action Level (as As)" As            |                                       |
|                     |         |     | Inorganic arsenic                   |                                       |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TLV-TWA | USA | "0.01 mg/m3 TWA (as As)"            | ACGIH - Threshold Limit Values - Time |
|                     |         |     | As Arsenic inorganic                | Weighted Averages (TLV-TWA)           |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TWA     | USA | "10 μg/m³ TWA (as As)" As           | U.S OSHA - Final PELs - Time          |
|                     |         |     | Arsenic, inorganic                  | Weighted Averages (TWAs)              |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TLV-TWA | USA | "0.01 mg/m3 TWA (as As)"            | ACGIH - Threshold Limit Values - Time |
|                     |         |     | As Arsenic inorganic                | Weighted Averages (TLV-TWA)           |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TWA     | USA | "10 μg/m³ TWA (as As)" As           | U.S OSHA - Final PELs - Time          |
|                     |         |     | Arsenic, inorganic                  | Weighted Averages (TWAs)              |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | PEL     | USA | "10 μg/m³ TWA (See 29               | U.S OSHA - Specifically Regulated     |
|                     |         |     | CFR 1910.1018; except               | Chemicals with PELs                   |
|                     |         |     | Arsine, as As); 5 μg/m³             |                                       |
|                     |         |     | Action Level (as As)" As            |                                       |
|                     |         |     | Inorganic arsenic                   |                                       |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TWA     | USA | "10 μg/m³ TWA (as As)" As           | U.S OSHA - Final PELs - Time          |
|                     |         |     | Arsenic, inorganic                  | Weighted Averages (TWAs)              |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TLV-TWA | USA | "0.01 mg/m³ TWA (as As)"            | ACGIH - Threshold Limit Values - Time |
|                     |         |     | As Arsenic inorganic                | Weighted Averages (TLV-TWA)           |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | PEL     | USA | "10 μg/m³ TWA (See 29               | U.S OSHA - Specifically Regulated     |
|                     |         |     | CFR 1910.1018; except               | Chemicals with PELs                   |
|                     |         |     | Arsine, as As); 5 μg/m³             |                                       |
|                     |         |     | Action Level (as As)" As            |                                       |
|                     |         |     | Inorganic arsenic                   |                                       |
|                     |         |     | compounds [RR-00065-7]              |                                       |

Product Number: RSPIKE1 Page 12 of 35



# **Safety Data Sheet**

| Arsenic (7440-38-2) | PEL     | USA | "10 μg/m³ TWA (See 29               | U.S OSHA - Specifically Regulated     |
|---------------------|---------|-----|-------------------------------------|---------------------------------------|
|                     |         |     | CFR 1910.1018; except               | Chemicals with PELs                   |
|                     |         |     | Arsine, as As); 5 μg/m <sup>3</sup> |                                       |
|                     |         |     | Action Level (as As)" As            |                                       |
|                     |         |     | Inorganic arsenic                   |                                       |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TLV-TWA | USA | "0.01 mg/m³ TWA (as As)"            | ACGIH - Threshold Limit Values - Time |
|                     |         |     | As Arsenic inorganic                | Weighted Averages (TLV-TWA)           |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TWA     | USA | "10 μg/m³ TWA (as As)" As           | U.S OSHA - Final PELs - Time          |
|                     |         |     | Arsenic, inorganic                  | Weighted Averages (TWAs)              |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TWA     | USA | "10 μg/m³ TWA (as As)" As           | U.S OSHA - Final PELs - Time          |
|                     |         |     | Arsenic, inorganic                  | Weighted Averages (TWAs)              |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TLV-TWA | USA | "0.01 mg/m³ TWA (as As)"            | ACGIH - Threshold Limit Values - Time |
|                     |         |     | As Arsenic inorganic                | Weighted Averages (TLV-TWA)           |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | PEL     | USA | "10 μg/m³ TWA (See 29               | U.S OSHA - Specifically Regulated     |
|                     |         |     | CFR 1910.1018; except               | Chemicals with PELs                   |
|                     |         |     | Arsine, as As); 5 μg/m <sup>3</sup> |                                       |
|                     |         |     | Action Level (as As)" As            |                                       |
|                     |         |     | Inorganic arsenic                   |                                       |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TLV-TWA | USA | 0.01 mg/m³ TWA                      | ACGIH - Threshold Limit Values - Time |
|                     |         |     |                                     | Weighted Averages (TLV-TWA)           |
| Arsenic (7440-38-2) | PEL     | USA | "10 μg/m³ TWA (See 29               | U.S OSHA - Specifically Regulated     |
|                     |         |     | CFR 1910.1018; except               | Chemicals with PELs                   |
|                     |         |     | Arsine, as As); 5 μg/m <sup>3</sup> |                                       |
|                     |         |     | Action Level (as As)" As            |                                       |
|                     |         |     | Inorganic arsenic                   |                                       |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TLV-TWA | USA | "0.01 mg/m³ TWA (as As)"            | ACGIH - Threshold Limit Values - Time |
|                     |         |     | As Arsenic inorganic                | Weighted Averages (TLV-TWA)           |
|                     |         |     | compounds [RR-00065-7]              |                                       |
| Arsenic (7440-38-2) | TWA     | USA | "10 μg/m³ TWA (as As)" As           | U.S OSHA - Final PELs - Time          |
|                     |         |     | Arsenic, inorganic                  | Weighted Averages (TWAs)              |
|                     |         |     | compounds [RR-00065-7]              |                                       |

Product Number: RSPIKE1 Page 13 of 35



# **Safety Data Sheet**

| Beryllium (7440-41-7) | TLV-TWA     | USA | "0.00005 mg/m³ TWA<br>(inhalable particulate<br>matter, as Be)" As Beryllium                           | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
|-----------------------|-------------|-----|--|--|
|                       |             |     | compounds [RR-00557-2]   |  |
| Beryllium (7440-41-7) | TWA         | USA | "0.2 µg/m³ TWA (as Be)" As<br>Beryllium compounds<br>[RR-00557-2]                                      | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs)             |
| Beryllium (7440-41-7) | PEL-Ceiling | USA | "2 μg/m³ Ceiling (as Be)" As<br>Beryllium compounds<br>[RR-00557-2]                                    | U.S OSHA - Final PELs - Ceiling<br>Limits                            |
| Beryllium (7440-41-7) | TLV-TWA     | USA | "0.00005 mg/m³ TWA<br>(inhalable particulate<br>matter, as Be)" As Beryllium<br>compounds [RR-00557-2] | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Beryllium (7440-41-7) | TWA         | USA | "0.2 μg/m³ TWA (as Be)" As<br>Beryllium compounds<br>[RR-00557-2]                                      | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs)             |
| Beryllium (7440-41-7) | PEL-Ceiling | USA | "2 μg/m³ Ceiling (as Be)" As<br>Beryllium compounds<br>[RR-00557-2]                                    | U.S OSHA - Final PELs - Ceiling<br>Limits                            |
| Beryllium (7440-41-7) | PEL         | USA | 0.2 μg/m³ TWA (See 29<br>CFR 1910.1024); 0.1 μg/m³<br>Action Level; 2.0 μg/m³<br>STEL (15 min)         | U.S OSHA - Specifically Regulated<br>Chemicals with PELs             |
| Beryllium (7440-41-7) | PEL-STEL    | USA | 2 μg/m³ STEL (see 29 CFR<br>1910.1024)   | U.S OSHA - Final PELs - Short Term<br>Exposure Limits                |
| Beryllium (7440-41-7) | TLV-TWA     | USA | 0.00005 mg/m³ TWA<br>(inhalable particulate<br>matter)   | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Beryllium (7440-41-7) | PEL-Ceiling | USA | 2 μg/m³ Ceiling  | U.S OSHA - Final PELs - Ceiling<br>Limits                            |
| Beryllium (7440-41-7) | TWA         | USA | 0.2 μg/m³ TWA  | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs)             |
| Beryllium (7440-41-7) | PEL-Ceiling | USA | "2 μg/m³ Ceiling (as Be)" As<br>Beryllium compounds<br>[RR-00557-2]                                    | U.S OSHA - Final PELs - Ceiling<br>Limits                            |
| Beryllium (7440-41-7) | TWA         | USA | "0.2 μg/m³ TWA (as Be)" As<br>Beryllium compounds<br>[RR-00557-2]                                      | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs)             |

Product Number: RSPIKE1 Page 14 of 35



# **Safety Data Sheet**

| Beryllium (7440-41-7) | TLV-TWA | USA | "0.00005 mg/m³ TWA<br>(inhalable particulate<br>matter, as Be)" As Beryllium<br>compounds [RR-00557-2]                            | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
|-----------------------|---------|-----|---|--|
| Cadmium (7440-43-9)   | PEL     | USA | "5 μg/m³ TWA (See 29 CFR<br>1910.1027, as Cd); 2.5<br>μg/m³ Action Level (as Cd)"<br>As Cadmium compounds<br>[RR-00559-4]         | U.S OSHA - Specifically Regulated<br>Chemicals with PELs             |
| Cadmium (7440-43-9)   | TLV-TWA | USA | "0.01 mg/m³ TWA (as Cd);<br>0.002 mg/m³ TWA<br>(respirable particulate<br>matter, as Cd)" As<br>Cadmium compounds<br>[RR-00559-4] | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Cadmium (7440-43-9)   | PEL     | USA | "5 μg/m³ TWA (See 29 CFR<br>1910.1027, as Cd); 2.5<br>μg/m³ Action Level (as Cd)"<br>As Cadmium compounds<br>[RR-00559-4]         | U.S OSHA - Specifically Regulated<br>Chemicals with PELs             |
| Cadmium (7440-43-9)   | TLV-TWA | USA | "0.01 mg/m³ TWA (as Cd);<br>0.002 mg/m³ TWA<br>(respirable particulate<br>matter, as Cd)" As<br>Cadmium compounds<br>[RR-00559-4] | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Cadmium (7440-43-9)   | TLV-TWA | USA | "0.01 mg/m³ TWA (as Cd);<br>0.002 mg/m³ TWA<br>(respirable particulate<br>matter, as Cd)" As<br>Cadmium compounds<br>[RR-00559-4] | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Cadmium (7440-43-9)   | PEL     | USA | "5 μg/m³ TWA (See 29 CFR<br>1910.1027, as Cd); 2.5<br>μg/m³ Action Level (as Cd)"<br>As Cadmium compounds<br>[RR-00559-4]         | U.S OSHA - Specifically Regulated<br>Chemicals with PELs             |

Product Number: RSPIKE1 Page 15 of 35



# **Safety Data Sheet**

| Cadmium (7440-43-9) | PEL        | USA  | "5 μg/m³ TWA (See 29 CFR                              | U.S OSHA - Specifically Regulated                     |
|---------------------|------------|------|---|---|
|                     |            |      | 1910.1027, as Cd); 2.5                                | Chemicals with PELs                                   |
|                     |            |      | μg/m³ Action Level (as Cd)"                           |   |
|                     |            |      | As Cadmium compounds                                  |   |
|                     |            |      | [RR-00559-4]  |   |
| Cadmium (7440-43-9) | TLV-TWA    | USA  | "0.01 mg/m³ TWA (as Cd);                              | ACGIH - Threshold Limit Values - Time                 |
|                     |            |      | 0.002 mg/m³ TWA                                       | Weighted Averages (TLV-TWA)                           |
|                     |            |      | (respirable particulate                               |   |
|                     |            |      | matter, as Cd)" As                                    |   |
|                     |            |      | Cadmium compounds                                     |   |
| Codmium (7440-40-0) | DEI        | LICA | [RR-00559-4]  | II C OCHA Chocifically Demyloted                      |
| Cadmium (7440-43-9) | PEL        | USA  | "5 µg/m³ TWA (See 29 CFR                              | U.S OSHA - Specifically Regulated Chemicals with PELs |
|                     |            |      | 1910.1027, as Cd); 2.5<br>μg/m³ Action Level (as Cd)" | Chemicals with FELS                                   |
|                     |            |      | As Cadmium compounds                                  |   |
|                     |            |      | [RR-00559-4]  |   |
| Cadmium (7440-43-9) | TLV-TWA    | USA  | "0.01 mg/m³ TWA (as Cd);                              | ACGIH - Threshold Limit Values - Time                 |
|                     | V 1 V V/ V | 30/1 | 0.002 mg/m³ TWA (d3 Gd),                              | Weighted Averages (TLV-TWA)                           |
|                     |            |      | (respirable particulate                               | rreignica / treiages (121 1171)                       |
|                     |            |      | matter, as Cd)" As                                    |   |
|                     |            |      | Cadmium compounds                                     |   |
|                     |            |      | [RR-00559-4]  |   |
| Cadmium (7440-43-9) | TLV-TWA    | USA  | "0.01 mg/m³ TWA (as Cd);                              | ACGIH - Threshold Limit Values - Time                 |
|                     |            |      | 0.002 mg/m <sup>3</sup> TWA                           | Weighted Averages (TLV-TWA)                           |
|                     |            |      | (respirable particulate                               |   |
|                     |            |      | matter, as Cd)" As                                    |   |
|                     |            |      | Cadmium compounds                                     |   |
|                     |            |      | [RR-00559-4]  |   |
| Cadmium (7440-43-9) | PEL        | USA  | "5 μg/m³ TWA (See 29 CFR                              | U.S OSHA - Specifically Regulated                     |
|                     |            |      | 1910.1027, as Cd); 2.5                                | Chemicals with PELs                                   |
|                     |            |      | μg/m³ Action Level (as Cd)"                           |   |
|                     |            |      | As Cadmium compounds                                  |   |
|                     |            |      | [RR-00559-4]  |   |
| Cadmium (7440-43-9) | PEL        | USA  | "5 μg/m³ TWA (See 29 CFR                              | U.S OSHA - Specifically Regulated                     |
|                     |            |      | 1910.1027, as Cd); 2.5                                | Chemicals with PELs                                   |
|                     |            |      | μg/m³ Action Level (as Cd)"                           |   |
|                     |            |      | As Cadmium compounds                                  |   |
|                     |            |      | [RR-00559-4]  |   |

Product Number: RSPIKE1 Page 16 of 35



# **Safety Data Sheet**

| Cadmium (7440-43-9) | TLV-TWA | USA | "0.01 mg/m³ TWA (as Cd);<br>0.002 mg/m³ TWA<br>(respirable particulate<br>matter, as Cd)" As<br>Cadmium compounds                 | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
|---------------------|---------|-----|---|--|
| Cadmium (7440-43-9) | PEL     | USA | [RR-00559-4]  "5 µg/m³ TWA (See 29 CFR 1910.1027, as Cd); 2.5   | U.S OSHA - Specifically Regulated Chemicals with PELs                |
|                     |         |     | µg/m³ Action Level (as Cd)"<br>As Cadmium compounds<br>[RR-00559-4]   |  |
| Cadmium (7440-43-9) | TLV-TWA | USA | "0.01 mg/m³ TWA (as Cd);<br>0.002 mg/m³ TWA<br>(respirable particulate<br>matter, as Cd)" As<br>Cadmium compounds<br>[RR-00559-4] | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Cadmium (7440-43-9) | PEL     | USA | "5 μg/m³ TWA (See 29 CFR<br>1910.1027, as Cd); 2.5<br>μg/m³ Action Level (as Cd)"<br>As Cadmium compounds<br>[RR-00559-4]         | U.S OSHA - Specifically Regulated<br>Chemicals with PELs             |
| Cadmium (7440-43-9) | TLV-TWA | USA | "0.01 mg/m³ TWA (as Cd);<br>0.002 mg/m³ TWA<br>(respirable particulate<br>matter, as Cd)" As<br>Cadmium compounds<br>[RR-00559-4] | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |
| Cadmium (7440-43-9) | PEL     | USA | 5 μg/m³ TWA (See 29 CFR<br>1910.1027); 2.5 μg/m³<br>Action Level  | U.S OSHA - Specifically Regulated<br>Chemicals with PELs             |
| Cadmium (7440-43-9) | TLV-TWA | USA | 0.01 mg/m³ TWA; 0.002<br>mg/m³ TWA (respirable<br>particulate matter)   | ACGIH - Threshold Limit Values - Time<br>Weighted Averages (TLV-TWA) |

Product Number: RSPIKE1 Page 17 of 35



# **Safety Data Sheet**

| Cadmium (7440-43-9) | PEL-Ceiling | USA | 0.3 mg/m³ Ceiling (applies            | U.S OSHA - Final PELs - Ceiling       |
|---------------------|-------------|-----|---------------------------------------|---------------------------------------|
| (                   | 3           |     | to any operations or sectors          | Limits                                |
|                     |             |     | for which the Cadmium                 |                                       |
|                     |             |     | standard is stayed or                 |                                       |
|                     |             |     | otherwise not in effect,              |                                       |
|                     |             |     | fume); 0.6 mg/m³ Ceiling              |                                       |
|                     |             |     | (applies to any operations            |                                       |
|                     |             |     | or sectors for which the              |                                       |
|                     |             |     | Cadmium standard is                   |                                       |
|                     |             |     | stayed or otherwise not in            |                                       |
|                     |             |     | effect, dust)                         |                                       |
| Cadmium (7440-43-9) | TWA         | USA | 5 μg/m³ TWA                           | U.S OSHA - Final PELs - Time          |
| , , ,               |             |     |                                       | Weighted Averages (TWAs)              |
| Cadmium (7440-43-9) | TLV-TWA     | USA | "0.01 mg/m3 TWA (as Cd);              | ACGIH - Threshold Limit Values - Time |
|                     |             |     | 0.002 mg/m³ TWA                       | Weighted Averages (TLV-TWA)           |
|                     |             |     | (respirable particulate               |                                       |
|                     |             |     | matter, as Cd)" As                    |                                       |
|                     |             |     | Cadmium compounds                     |                                       |
|                     |             |     | [RR-00559-4]                          |                                       |
| Cadmium (7440-43-9) | PEL         | USA | "5 μg/m³ TWA (See 29 CFR              | U.S OSHA - Specifically Regulated     |
|                     |             |     | 1910.1027, as Cd); 2.5                | Chemicals with PELs                   |
|                     |             |     | μg/m³ Action Level (as Cd)"           |                                       |
|                     |             |     | As Cadmium compounds                  |                                       |
|                     |             |     | [RR-00559-4]                          |                                       |
| Cadmium (7440-43-9) | PEL         | USA | "5 μg/m³ TWA (See 29 CFR              | U.S OSHA - Specifically Regulated     |
|                     |             |     | 1910.1027, as Cd); 2.5                | Chemicals with PELs                   |
|                     |             |     | μg/m³ Action Level (as Cd)"           |                                       |
|                     |             |     | As Cadmium compounds                  |                                       |
|                     |             |     | [RR-00559-4]                          |                                       |
| Cadmium (7440-43-9) | TLV-TWA     | USA | "0.01 mg/m3 TWA (as Cd);              | ACGIH - Threshold Limit Values - Time |
|                     |             |     | 0.002 mg/m <sup>3</sup> TWA           | Weighted Averages (TLV-TWA)           |
|                     |             |     | (respirable particulate               |                                       |
|                     |             |     | matter, as Cd)" As                    |                                       |
|                     |             |     | Cadmium compounds                     |                                       |
|                     |             |     | [RR-00559-4]                          |                                       |
| Cobalt (7440-48-4)  | TWA         | USA | 0.1 mg/m³ TWA (dust and               | U.S OSHA - Final PELs - Time          |
|                     |             |     | fume)                                 | Weighted Averages (TWAs)              |
| Cobalt (7440-48-4)  | TLV-TWA     | USA | 0.02 mg/m <sup>3</sup> TWA (inhalable | ACGIH - Threshold Limit Values - Time |
|                     |             |     | particulate matter)                   | Weighted Averages (TLV-TWA)           |
| Cobalt (7440-48-4)  | TLV-TWA     | USA | 0.02 mg/m <sup>3</sup> TWA (inhalable | ACGIH - Threshold Limit Values - Time |
|                     |             |     | particulate matter, as Co)            | Weighted Averages (TLV-TWA)           |

Product Number: RSPIKE1 Page 18 of 35



# **Safety Data Sheet**

| Copper (7440-50-8)            | TWA         | USA | 0.1 mg/m³ TWA (fume); 1          | U.S OSHA - Final PELs - Time          |
|-------------------------------|-------------|-----|----------------------------------|---------------------------------------|
|                               |             |     | mg/m³ TWA (dust and mist)        | Weighted Averages (TWAs)              |
| Copper (7440-50-8)            | TLV-TWA     | USA | 0.2 mg/m³ TWA (fume)             | ACGIH - Threshold Limit Values - Time |
|                               |             |     |                                  | Weighted Averages (TLV-TWA)           |
| Copper (7440-50-8)            | TLV-TWA     | USA | "1 mg/m3 TWA (dust and           | ACGIH - Threshold Limit Values - Time |
|                               |             |     | mist, as Cu)" As Copper          | Weighted Averages (TLV-TWA)           |
|                               |             |     | compounds [RR-00595-8]           |                                       |
| Copper (7440-50-8)            | TLV-TWA     | USA | "1 mg/m³ TWA (dust and           | ACGIH - Threshold Limit Values - Time |
|                               |             |     | mist, as Cu)" As Copper          | Weighted Averages (TLV-TWA)           |
|                               |             |     | compounds [RR-00595-8]           |                                       |
| Vanadium (7440-62-2)          | PEL-Ceiling | USA | 0.5 mg/m <sup>3</sup> Ceiling    | U.S OSHA - Final PELs - Ceiling       |
|                               |             |     | (respirable dust, as V2O5);      | Limits                                |
|                               |             |     | 0.1 mg/m³ Ceiling (fume, as      |                                       |
|                               |             |     | V2O5)                            |                                       |
| Hydrofluoric Acid (7664-39-3) | TWA         | USA | "2.5 mg/m³ TWA (as F)" As        | U.S OSHA - Final PELs - Time          |
|                               |             |     | Fluorides [RR-02792-9]           | Weighted Averages (TWAs)              |
| Hydrofluoric Acid (7664-39-3) | TLV-TWA     | USA | "2.5 mg/m³ TWA (as F)" As        | ACGIH - Threshold Limit Values - Time |
|                               |             |     | Fluorides [RR-02792-9]           | Weighted Averages (TLV-TWA)           |
| Hydrofluoric Acid (7664-39-3) | TLV-TWA     | USA | 0.5 ppm TWA (as F)               | ACGIH - Threshold Limit Values - Time |
|                               |             |     |                                  | Weighted Averages (TLV-TWA)           |
| Hydrofluoric Acid (7664-39-3) | TWA         | USA | 3 ppm TWA (as F)                 | U.S OSHA - Final PELs - Time          |
|                               |             |     |                                  | Weighted Averages (TWAs)              |
| Hydrofluoric Acid (7664-39-3) | TLV-Ceiling | USA | 2 ppm Ceiling (as F)             | ACGIH - Threshold Limit Values -      |
|                               |             |     |                                  | Ceilings (TLV-C)                      |
| Hydrofluoric Acid (7664-39-3) | TLV-TWA     | USA | 2.5 mg/m³ TWA (as F)             | ACGIH - Threshold Limit Values - Time |
|                               |             |     |                                  | Weighted Averages (TLV-TWA)           |
| Hydrofluoric Acid (7664-39-3) | TWA         | USA | 2.5 mg/m <sup>3</sup> TWA (as F) | U.S OSHA - Final PELs - Time          |
|                               |             |     |                                  | Weighted Averages (TWAs)              |
| Nitric Acid (7697-37-2)       | TWA         | USA | 2 ppm TWA; 5 mg/m³ TWA           | U.S OSHA - Final PELs - Time          |
|                               |             |     |                                  | Weighted Averages (TWAs)              |
| Nitric Acid (7697-37-2)       | TLV-TWA     | USA | 2 ppm TWA                        | ACGIH - Threshold Limit Values - Time |
|                               |             |     |                                  | Weighted Averages (TLV-TWA)           |
| Nitric Acid (7697-37-2)       | TLV-STEL    | USA | 4 ppm STEL                       | ACGIH - Threshold Limit Values -      |
|                               |             |     |                                  | Short Term Exposure Limits            |
|                               |             |     |                                  | (TLV-STEL)                            |
| Selenium (7782-49-2)          | TLV-TWA     | USA | "0.2 mg/m³ TWA (as Se)"          | ACGIH - Threshold Limit Values - Time |
|                               |             |     | As Selenium compounds            | Weighted Averages (TLV-TWA)           |
|                               |             |     | [RR-00612-2]                     |                                       |
| Selenium (7782-49-2)          | TWA         | USA | "0.2 mg/m³ TWA (as Se)"          | U.S OSHA - Final PELs - Time          |
|                               |             |     | As Selenium compounds            | Weighted Averages (TWAs)              |
|                               |             |     | [RR-00612-2]                     |                                       |

Product Number: RSPIKE1 Page 19 of 35



# **Safety Data Sheet**

| Selenium (7782-49-2)         | TLV-TWA      | USA | "0.2 mg/m³ TWA (as Se)"            | ACGIH - Threshold Limit Values - Time |
|------------------------------|--------------|-----|------------------------------------|---------------------------------------|
|                              |              |     | As Selenium compounds [RR-00612-2] | Weighted Averages (TLV-TWA)           |
| Selenium (7782-49-2)         | TWA          | USA | "0.2 mg/m³ TWA (as Se)"            | U.S OSHA - Final PELs - Time          |
|                              |              |     | As Selenium compounds              | Weighted Averages (TWAs)              |
|                              |              |     | [RR-00612-2]                       |                                       |
| Selenium (7782-49-2)         | TLV-TWA      | USA | "0.2 mg/m³ TWA (as Se)"            | ACGIH - Threshold Limit Values - Time |
|                              |              |     | As Selenium compounds              | Weighted Averages (TLV-TWA)           |
|                              |              |     | [RR-00612-2]                       |                                       |
| Selenium (7782-49-2)         | TWA          | USA | "0.2 mg/m³ TWA (as Se)"            | U.S OSHA - Final PELs - Time          |
|                              |              |     | As Selenium compounds              | Weighted Averages (TWAs)              |
|                              |              |     | [RR-00612-2]                       |                                       |
| Selenium (7782-49-2)         | TWA          | USA | "0.2 mg/m³ TWA (as Se)"            | U.S OSHA - Final PELs - Time          |
|                              |              |     | As Selenium compounds              | Weighted Averages (TWAs)              |
|                              |              |     | [RR-00612-2]                       |                                       |
| Selenium (7782-49-2)         | TLV-TWA      | USA | "0.2 mg/m³ TWA (as Se)"            | ACGIH - Threshold Limit Values - Time |
|                              |              |     | As Selenium compounds              | Weighted Averages (TLV-TWA)           |
|                              |              |     | [RR-00612-2]                       |                                       |
| Selenium (7782-49-2)         | TLV-TWA      | USA | "0.2 mg/m³ TWA (as Se)"            | ACGIH - Threshold Limit Values - Time |
|                              |              |     | As Selenium compounds              | Weighted Averages (TLV-TWA)           |
|                              |              |     | [RR-00612-2]                       |                                       |
| Selenium (7782-49-2)         | TWA          | USA | "0.2 mg/m³ TWA (as Se)"            | U.S OSHA - Final PELs - Time          |
|                              |              |     | As Selenium compounds              | Weighted Averages (TWAs)              |
|                              |              |     | [RR-00612-2]                       |                                       |
| Selenium (7782-49-2)         | TWA          | USA | "0.2 mg/m³ TWA (as Se)"            | U.S OSHA - Final PELs - Time          |
|                              |              |     | As Selenium compounds              | Weighted Averages (TWAs)              |
|                              |              |     | [RR-00612-2]                       |                                       |
| Selenium (7782-49-2)         | TLV-TWA      | USA | "0.2 mg/m³ TWA (as Se)"            | ACGIH - Threshold Limit Values - Time |
|                              |              |     | As Selenium compounds              | Weighted Averages (TLV-TWA)           |
|                              |              |     | [RR-00612-2]                       |                                       |
| Selenium (7782-49-2)         | TLV-TWA      | USA | 0.2 mg/m³ TWA                      | ACGIH - Threshold Limit Values - Time |
|                              |              |     |                                    | Weighted Averages (TLV-TWA)           |
| Selenium (7782-49-2)         | TWA          | USA | "0.2 mg/m³ TWA (as Se)"            | U.S OSHA - Final PELs - Time          |
|                              |              |     | As Selenium compounds              | Weighted Averages (TWAs)              |
|                              |              |     | [RR-00612-2]                       |                                       |
| Selenium (7782-49-2)         | TLV-TWA      | USA | "0.2 mg/m³ TWA (as Se)"            | ACGIH - Threshold Limit Values - Time |
|                              |              |     | As Selenium compounds              | Weighted Averages (TLV-TWA)           |
|                              |              |     | [RR-00612-2]                       |                                       |
| Chromium Nitrate Nonahydrate | e (7789-(TWA | USA | "0.5 mg/m3 TWA (as Cr)" As         | U.S OSHA - Final PELs - Time          |
|                              |              |     | Chromium(III) compounds            | Weighted Averages (TWAs)              |
|                              |              |     | [RR-03889-1]                       |                                       |

Product Number: RSPIKE1 Page 20 of 35



## **Safety Data Sheet**

| Chromium Nitrate Nonahydrate (7789-(TWA | USA | "0.5 mg/m³ TWA (as Cr)" As<br>Chromium(III) compounds<br>[RR-03889-1] | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs) |
|---|-----|---|--|
| Chromium Nitrate Nonahydrate (7789-(TWA | USA | 0.5 mg/m³ TWA (as Cr)   | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs) |
| Chromium Nitrate Nonahydrate (7789-(TWA | USA | "0.5 mg/m³ TWA (as Cr)" As<br>Chromium(III) compounds<br>[RR-03889-1] | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs) |
| Chromium Nitrate Nonahydrate (7789-(TWA | USA | "0.5 mg/m³ TWA (as Cr)" As<br>Chromium(III) compounds<br>[RR-03889-1] | U.S OSHA - Final PELs - Time<br>Weighted Averages (TWAs) |

#### 8.2. Exposure Controls

Engineering Controls: Use only outdoors or in a well-ventilated area. No specific controls are needed. Normal room ventilation is

adequate.

**Respiratory Protection:** In case of inadequate ventilation wear respiratory protection. Normal room ventilation is adequate.

**Skin Protection:** Wear protective gloves and eye protection. Chemical resistant gloves. **Eye Protection:** Wear protective gloves and eye protection. Safety glasses or goggles.

#### 8.3. Personal Protective Equipment

Wear protective gloves and eye protection. In case of inadequate ventilation wear respiratory protection. Normal room ventilation is adequate. Chemical resistant gloves. Safety glasses or goggles.

Product Number: RSPIKE1 Page 21 of 35



### **SECTION 9: Physical and Chemical Properties**

#### 9.1. Basic Physical and Chemical Properties

Appearance: Colorless liquid

Physical State: Liquid

Odor: Data not available.

Odor Threshold: Data not available.

pH: Acidic

Melting/Freezing Point: Approximately 0°C

Initial Boiling Point/Range: Approximately 100°C - Approximately 100°C

Flash Point: Data not available.

Evaporation Rate: Data not available.

Flammability: Data not available.

Flammability/Explosive Limits: Data not available.

Vapor Pressure: Data not available.

Vapor Density: Data not available.

Relative Density: 1.03

Solubility: Miscible

Partition Coefficient: Data not available.

Auto-Ignition Temperature: Data not available.

**Decomposition Temperature:** Data not available.

Viscosity: Data not available.

**Explosive Properties:** Data not available.

Oxidizing Properties: Data not available.

## **SECTION 10: Stability and Reactivity**

#### 10.1. Reactivity and Chemical Stability

Stable under normal conditions of use and storage.

#### 10.2. Possibility of Hazardous Reactions

Data not available.

### 10.3. Conditions to Avoid and Incompatible Materials

Keep only in original container. Strong bases, metallic powders.

#### 10.4. Hazardous Decomposition Products

Will not occur.

Product Number: RSPIKE1 Page 22 of 35

### **SECTION 11: Toxicological Information**

#### 11.1. Information on Toxicological Effects

#### **Acute Toxicity - Oral Exposure:**

Not applicable.

#### **Acute Toxicity - Dermal Exposure:**

Not applicable.

#### **Acute Toxicity - Inhalation Exposure:**

Fatal if inhaled. Do not breathe fumes, mist, vapors, or spray. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. Specific treatment is urgent (Wash areas of contact with water.). Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents in accordance with local, state, federal and international regulations.

#### **Acute Toxicity - Other Information:**

LDLo, Oral, Human: 430 mg/kg (Nitric Acid), details of toxic effects not reported other than lethal dose value. 2330 mg/kg (Cadmium) details of toxic effects not reported other than lethal dose value. LD50, Oral, Rat: 763 mg/kg (Arsenic), behavioral and gastrointestinal effects noted.

#### **Skin Corrosion and Irritation:**

Causes severe skin burns and eye damage. Do not breathe fumes, mist, vapors, or spray. Wash arms, hands and face thoroughly after handling. Wear protective gloves and eye protection. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. Specific treatment (Wash areas of contact with water.). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents in accordance with local, state, federal and international regulations.

#### Serious Eye Damage and Irritation:

Causes serious eye damage. Wear protective gloves and eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

#### **Respiratory Sensitization:**

Not applicable.

#### Skin Sensitization:

Not applicable.

#### **Germ Cell Mutagenicity:**

Not applicable.

#### Carcinogenicity:

Not applicable.

#### **Reproductive Toxicity:**

Not applicable.

#### **Specific Target Organ Toxicity from Single Exposure:**

Not applicable.

Product Number: RSPIKE1 Page 23 of 35

#### **Specific Target Organ Toxicity from Repeated Exposure:**

Not applicable.

#### **Aspiration Hazard:**

Not applicable.

#### **Additional Toxicology Information:**

Data not available.

### **SECTION 12: Ecological Information**

#### 12.1. Ecotoxicity

Toxic to aquatic life. Avoid release to the environment. Dispose of contents in accordance with local, state, federal and international regulations. Toxic to aquatic life with long lasting effects. Avoid release to the environment. Collect spillage. Dispose of contents in accordance with local, state, federal and international regulations.

#### 12.2. Persistence and Degradability

Data not available.

#### 12.3. Bioaccumulative Potential

Data not available.

#### 12.4. Mobility in Soil

Data not available.

#### 12.5. Other Adverse Ecological Effects

Data not available.

## **SECTION 13: Disposal Considerations**

#### 13.1. Waste Treatment Methods

Data not available.

Product Number: RSPIKE1 Page 24 of 35



### **SECTION 14: Transportation Information**

14.1. Transportation by Land-Department of Transportation (DOT, United States of America)

Sizes: 100 mL

UN Number: UN3264

Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, n.o.s. (Nitric Acid)

Hazard Class: 8

Packing Group: |||

Hazard Label(s):



14.2. Transportation by Air - International Air Transport Association (IATA)

Sizes: 100 mL

UN Number: UN3264

**Proper Shipping Name:** Corrosive Liquid, Acidic, Inorganic, n.o.s. (Nitric Acid)

Hazard Class: 8

Packing Group: |||

Hazard Label(s):



14.3 Transportation of Dangerous Goods (TDG, Canada)

Sizes: 100 mL

UN Number: UN3264

Proper Shipping Name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

Hazard Class: 8

Packing Group: |||

Hazard Label(s):



Product Number: RSPIKE1 Page 25 of 35



### **SECTION 15: Regulatory Information**

#### 15.1. Occupational Safety and Health Administration (OSHA) Hazards

Lead (CAS # 7439-92-1): 30 μg/m3 Action Level (See 29 CFR 1910.1025); 50 μg/m3 TWA (See 29 CFR 1910.1025)

Arsenic (CAS # 7440-38-2): "10 μg/m3 TWA (See 29 CFR 1910.1018, except Arsine, as As); 5 μg/m3 Action Level (See 29 CFR 1910.1018, except Arsine, as As)" As Inorganic arsenic compounds [RR-00065-7]

Beryllium (CAS # 7440-41-7): 0.2 μg/m3 TWA (See 29 CFR 1910.1024); 0.1 μg/m3 Action Level (See 29 CFR 1910.1024); 2.0 μg/m3 STEL (See 29 CFR 1910.1024, 15 min)

Cadmium (CAS # 7440-43-9): "5 μg/m3 TWA (See 29 CFR 1910.1027, as Cd); 2.5 μg/m3 Action Level (as Cd)" As Cadmium compounds [RR-00559-4]

Cadmium (CAS # 7440-43-9): 5 μg/m3 TWA (See 29 CFR 1910.1027); 2.5 μg/m3 Action Level

#### 15.2. Superfund Amendments and Reauthorization Act (SARA) 302 Extremely Hazardous Substances

Hydrofluoric Acid (CAS # 7664-39-3): 100 lb EPCRA RQ Hydrofluoric Acid (CAS # 7664-39-3): 100 lb TPQ

Nitric Acid (CAS # 7697-37-2): 1000 lb EPCRA RQ Nitric Acid (CAS # 7697-37-2): 1000 lb TPQ

### 15.3. Superfund Amendments and Reauthorization Act (SARA) 311/312 Hazardous Chemicals

Antimony Trioxide (CAS # 1309-64-4): 1000 lb final RQ; 454 kg final RQ

Lead (CAS # 7439-92-1): 10 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100  $\mu$ m); 4.54 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100  $\mu$ m)

Nickel (CAS # 7440-02-0): 100 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is  $>100 \mu m$ ); 45.4 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is  $>100 \mu m$ )

Silver (CAS # 7440-22-4): 1 lb final RQ; 0.454 kg final RQ

Silver (CAS # 7440-22-4): 1000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100  $\mu$ m); 454 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100  $\mu$ m)

Thallium (CAS # 7440-28-0): 1000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm); 454 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm)

Arsenic (CAS # 7440-38-2): 1 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100  $\mu$ m); 0.454 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100  $\mu$ m)

Arsenic (CAS # 7440-38-2): 1 lb final RQ; 0.454 kg final RQ

Beryllium (CAS # 7440-41-7): 10 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the soli

Product Number: RSPIKE1 Page 26 of 35



## **Safety Data Sheet**

#### 15.4. Superfund Amendments and Reauthorization Act (SARA) 313 Toxic Release Inventory (TRI)

Barium Nitrate (CAS # 10022-31-8): "1.0 % de minimis concentration (includes any unique chemical substance that contains Barium as part of that chemical's infrastructure except for Barium sulfate CAS 7727-43-7, listed under Chemical Category N040)" As Barium compounds [RR-00555-0] Barium Nitrate (CAS # 10022-31-8): "1.0 % de minimis concentration (includes any unique chemical substance that contains Barium as part of that chemical's infrastructure except for Barium sulfate CAS 7727-43-7, listed under Chemical Category N040)" As Barium compounds [RR-00555-0]; "1.0 % de minimis concentration (reportable only when in aqueous solution, listed under Chemical Category N511)" As Nitrate compounds, water dissociable [RR-03804-0]

Barium Nitrate (CAS # 10022-31-8): 1.0 % de minimis concentration (includes any unique chemical substance that contains Barium as part of that chemical's infrastructure except for Barium sulfate CAS 7727-43-7, listed under Chemical Category N040)

Barium Nitrate (CAS # 10022-31-8): 1.0 % de minimis concentration (reportable only when in aqueous solution, listed under Chemical Category N511)

Antimony Trioxide (CAS # 1309-64-4): "1.0 % de minimis concentration (includes any unique chemical substance that contains Antimony as part of that chemical's infrastructure, listed under Chemical Category N010)" As Antimony compounds [RR-00585-6]

Antimony Trioxide (CAS # 1309-64-4): 1.0 % de minimis concentration (includes any unique chemical substance that contains Antimony as part of that chemical's infrastructure, listed under Chemical Category N010)

Lead (CAS # 7439-92-1): 0.1 % Supplier notification limit; 0.1 % de minimis concentration (when contained in stainless steel, brass, or bronze)
Lead (CAS # 7439-92-1): 100 lb RT (this lower threshold does not apply to lead when it is contained in stainless steel, brass or bronze alloy)
Manganese (CAS # 7439-96-5): "1.0 % de minimis concentration (includes any unique chemical substance that contains Manganese as p

### 15.5. Massachusetts Right-to-Know Substance List

Barium Nitrate (CAS # 10022-31-8): Present

Antimony Trioxide (CAS # 1309-64-4): Present

Lead (CAS # 7439-92-1): Teratogen Manganese (CAS # 7439-96-5): Present

Nickel (CAS # 7440-02-0): Carcinogen; Extraordinarily hazardous

Silver (CAS # 7440-22-4): Present Thallium (CAS # 7440-28-0): Present

Arsenic (CAS # 7440-38-2): Carcinogen; Extraordinarily hazardous Beryllium (CAS # 7440-41-7): Carcinogen; Extraordinarily hazardous Cadmium (CAS # 7440-43-9): Carcinogen; Extraordinarily hazardous

Cobalt (CAS # 7440-48-4): Present Copper (CAS # 7440-50-8): Present

Vanadium (CAS # 7440-62-2): Present (dust and fume)

Zinc (CAS # 7440-66-6): Present

Hydrofluoric Acid (CAS # 7664-39-3): Extraordinarily hazardous Nitric Acid (CAS # 7697-37-2): Extraordinarily hazardous

Selenium (CAS # 7782-49-2): Present

Product Number: RSPIKE1 Page 27 of 35



## **Safety Data Sheet**

#### 15.6. Pennsylvania Right-to-Know Hazardous Substances

Barium Nitrate (CAS # 10022-31-8): "Environmental hazard" As Barium compounds [RR-00555-0]

Barium Nitrate (CAS # 10022-31-8): "Present" As Barium compounds [RR-00555-0]

Barium Nitrate (CAS # 10022-31-8): Environmental hazard

Barium Nitrate (CAS # 10022-31-8): Present

Antimony Trioxide (CAS # 1309-64-4): "Environmental hazard" As Antimony compounds [RR-00585-6]

Antimony Trioxide (CAS # 1309-64-4): "Present" As Antimony compounds [RR-00585-6]

Antimony Trioxide (CAS # 1309-64-4): Environmental hazard

Antimony Trioxide (CAS # 1309-64-4): Present Lead (CAS # 7439-92-1): Environmental hazard

Lead (CAS # 7439-92-1): Present

Manganese (CAS # 7439-96-5): "Environmental hazard" As Manganese compounds [RR-00602-0]

Manganese (CAS # 7439-96-5): "Present" As Manganese compounds [RR-00602-0]

Manganese (CAS # 7439-96-5): Environmental hazard

Manganese (CAS # 7439-96-5): Present

Nickel (CAS # 7440-02-0): "Environmental hazard" As Nickel compounds [RR-00800-4]

Nickel (CAS # 7440-02-0): "Present" As Nickel compounds [RR-00800-4]

Nickel (CAS # 7440-02-0): Environmental hazard

Nickel (CAS # 7440-02-0): Environmental hazard; Special hazardous substance

Nickel (CAS # 7440-02-0): Present

Silver (CAS # 7440-22-4): Environmental hazard

Silver (CAS # 7440-22-4): Present

Thallium (CAS # 7440-28-0): "Environmental hazard" As Thallium compounds [RR-00575-4]

Thallium (CAS # 7440-28-0): "Present" As Thallium compounds [RR-00575-4]

Thallium (CAS # 7440-28-0): Environmental hazard

Thallium (CAS # 7440-28-0): Present

Arsenic (CAS # 7440-38-2): "Environmental hazard" As Arsenic compounds [RR-00625-7]

Arsenic (CAS # 7440-38-2): "Present" As Arsenic compounds [RR-00625-7]

Arsenic (CAS # 7440-38-2): Environmental hazard (including inorganic); Special hazardous substance

Arsenic (CAS # 7440-38-2): Present

Arsenic (CAS # 7440-38-2): Present (including inorganic)

Beryllium (CAS # 7440-41-7): "Environmental hazard" As Beryllium compounds [RR-00557-2]

Beryllium (CAS # 7440-41-7): "Present" As Beryllium compou

Product Number: RSPIKE1 Page 28 of 35

## **Safety Data Sheet**

### 15.7. New Jersey Worker and Community Right-to-Know Components

Barium Nitrate (CAS # 10022-31-8): "SN 2146 500 lb TPQ (except Barium sulfate CAS number 7727-43-7, Category Code N040. Includes any unique chemical substance that contains the named metal as part of that chemical structure)" As Barium compounds [RR-00555-0]

Barium Nitrate (CAS # 10022-31-8): "SN 2146 500 lb TPQ (except Barium sulfate CAS number 7727-43-7, Category Code N040. Includes any unique chemical substance that contains the named metal as part of that chemical structure)" As Barium compounds [RR-00555-0];

"SN 3722 500 lb TPQ (water dissociable, Category Code N511)" As Nitrate compounds [RR-01770-9]

Barium Nitrate (CAS # 10022-31-8): "sn 2146" As Barium compounds [RR-00555-0]

Barium Nitrate (CAS # 10022-31-8): "SN 3722 500 lb TPQ (water dissociable, Category Code N511)" As Nitrate compounds [RR-01770-9]

Barium Nitrate (CAS # 10022-31-8): "sn 3722" As Nitrate compounds [RR-01770-9]

Barium Nitrate (CAS # 10022-31-8): sn 0186 Barium Nitrate (CAS # 10022-31-8): sn 2146

Barium Nitrate (CAS # 10022-31-8): SN 2146 500 lb TPQ (except Barium sulfate CAS number 7727-43-7, Category Code N040. Includes any unique chemical substance that contains the named metal as part of that chemical structure)

Barium Nitrate (CAS # 10022-31-8): sn 3722

Barium Nitrate (CAS # 10022-31-8): SN 3722 500 lb TPQ (water dissociable, Category Code N511)

Antimony Trioxide (CAS # 1309-64-4): "SN 2223 500 lb TPQ (Category Code N010. Includes any unique chemical substance that contains the named metal as part of that chemical structure)" As Antimony compounds [RR-00585-6]

Antimony Trioxide (CAS # 1309-64-4): "sn 2223" As Antimony compounds [RR-00585-6]

Antimony Trioxide (CAS # 1309-64-4): carcinogen

Antimony Trioxide (CAS # 1309-64-4): sn 0149

Antimony Trioxide (CAS # 1309-64-4): sn 2223

Antimony Trioxide (CAS # 1309-64-4): SN 2223 500 lb TPQ (Category Code N010. Includes any unique chemical substance that contains the named metal as part of that chemical structure)

Lead (CAS # 7439-92-1): carcin

Product Number: RSPIKE1 Page 29 of 35

#### 15.8. California Proposition 65

Antimony Trioxide (CAS # 1309-64-4): carcinogen, 10/1/1990

Lead (CAS # 7439-92-1): 15 μg/day NSRL (oral) Lead (CAS # 7439-92-1): carcinogen, 10/1/1992

Lead (CAS # 7439-92-1): developmental toxicity, 2/27/1987 Lead (CAS # 7439-92-1): female reproductive toxicity 2/27/87 Lead (CAS # 7439-92-1): male reproductive toxicity, 2/27/87

Nickel (CAS # 7440-02-0): "carcinogen, 5/7/2004" As Nickel compounds [RR-00800-4]

Nickel (CAS # 7440-02-0): carcinogen, 10/1/1989 (metallic)

Arsenic (CAS # 7440-38-2): "0.06 µg/day NSRL (inhalation, listed under Arsenic); 10 µg/day NSRL (except inhalation, listed under Arsenic)" As

Arsenic, inorganic compounds [RR-00065-7]

Arsenic (CAS # 7440-38-2): "carcinogen, 2/27/1987" As Arsenic, inorganic compounds [RR-00065-7]

Arsenic (CAS # 7440-38-2): 0.06 µg/day NSRL (inhalation); 10 µg/day NSRL (except inhalation)

Beryllium (CAS # 7440-41-7): "carcinogen, 10/1/1987" As Beryllium compounds [RR-00557-2]

Beryllium (CAS # 7440-41-7): 0.1 μg/day NSRL Beryllium (CAS # 7440-41-7): carcinogen, 10/1/1987

Cadmium (CAS # 7440-43-9): "carcinogen, 10/1/1987" As Cadmium compounds [RR-00559-4]

Cadmium (CAS # 7440-43-9): 0.05 µg/day NSRL (inhalation)

Cadmium (CAS # 7440-43-9): carcinogen, 10/1/1987

Cadmium (CAS # 7440-43-9): developmental toxicity, 5/1/1997 Cadmium (CAS # 7440-43-9): male reproductive toxicity, 5/1/97 Cobalt (CAS # 7440-48-4): carcinogen, 7/1/1992 (powder)

Product Number: RSPIKE1 Page 30 of 35



#### 15.9. Canada Domestic Substances List / Non-Domestic Substances List (DSL/NDSL)

Barium Nitrate (CAS # 10022-31-8): Present (DSL)

Antimony Trioxide (CAS # 1309-64-4): Present (DSL)

Iron (CAS # 7439-89-6): Present (DSL)

Lead (CAS # 7439-92-1): Present (DSL)

Manganese (CAS # 7439-96-5): Present (DSL)

Nickel (CAS # 7440-02-0): Present (DSL)

Silver (CAS # 7440-22-4): Present (DSL)

Thallium (CAS # 7440-28-0): Present (DSL)

Arsenic (CAS # 7440-38-2): Present (DSL)

Beryllium (CAS # 7440-41-7): Present (DSL)

Cadmium (CAS # 7440-43-9): Present (DSL)

Cobalt (CAS # 7440-48-4): Present (DSL)

Copper (CAS # 7440-50-8): Present (DSL)

Vanadium (CAS # 7440-62-2): Present (DSL)

Zinc (CAS # 7440-66-6): Present (DSL)

Hydrofluoric Acid (CAS # 7664-39-3): Present (DSL)

Nitric Acid (CAS # 7697-37-2): Present (DSL)

Water (CAS # 7732-18-5): Present (DSL)

Selenium (CAS # 7782-49-2): Present (DSL)

Aluminum Nitrate Nonahydrate (CAS # 7784-27-2): Present (DSL)

Chromium Nitrate Nonahydrate (CAS # 7789-02-8): Present (DSL)

#### 15.10. United States of America Toxic Substances Control Act (TSCA) List

All components of this solution are listed as active on the TSCA Inventory or are mixtures (hydrates) of active items listed on the TSCA Inventory.

Product Number: RSPIKE1 Page 31 of 35



## **Safety Data Sheet**

Barium Nitrate (CAS # 10022-31-8): Present (ACTIVE)

Antimony Trioxide (CAS # 1309-64-4): Present (ACTIVE)

Iron (CAS # 7439-89-6): Present (ACTIVE)

Lead (CAS # 7439-92-1): Present (ACTIVE)

Manganese (CAS # 7439-96-5): Present (ACTIVE)

Nickel (CAS # 7440-02-0): Present (ACTIVE)

Silver (CAS # 7440-22-4): Present (ACTIVE)

Thallium (CAS # 7440-28-0): Present (ACTIVE)

Arsenic (CAS # 7440-38-2): Present (ACTIVE)

Beryllium (CAS # 7440-41-7): Present (ACTIVE)

Cadmium (CAS # 7440-43-9): Present (ACTIVE)

Cobalt (CAS # 7440-48-4): Present (ACTIVE)

Copper (CAS # 7440-50-8): Present (ACTIVE)

Vanadium (CAS # 7440-62-2): Present (ACTIVE)

Zinc (CAS # 7440-66-6): Present (ACTIVE)

Hydrofluoric Acid (CAS # 7664-39-3): Present (ACTIVE)

Nitric Acid (CAS # 7697-37-2): Present (ACTIVE)

Water (CAS # 7732-18-5): Present (ACTIVE)

Selenium (CAS # 7782-49-2): Present (ACTIVE)

Aluminum Nitrate Nonahydrate (CAS # 7784-27-2): Present (ACTIVE)

Chromium Nitrate Nonahydrate (CAS # 7789-02-8): Present (ACTIVE)

Product Number: RSPIKE1 Page 32 of 35



15.11. European Inventory of Existing Commercial Chemical Substances (EINECS), European List of Notified Chemical Substances (ELINCS), and No Longer Polymers (NLP)

Barium Nitrate (CAS # 10022-31-8): 233-020-5

Antimony Trioxide (CAS # 1309-64-4): 215-175-0

Antimony Trioxide (CAS # 1309-64-4): 215-474-6

Iron (CAS # 7439-89-6): 231-096-4

Lead (CAS # 7439-92-1): 231-100-4

Manganese (CAS # 7439-96-5): 231-105-1

Nickel (CAS # 7440-02-0): 231-111-4

Silver (CAS # 7440-22-4): 231-131-3

Thallium (CAS # 7440-28-0): 231-138-1

Arsenic (CAS # 7440-38-2): 231-148-6

Beryllium (CAS # 7440-41-7): 231-150-7

Cadmium (CAS # 7440-43-9): 231-152-8

Cobalt (CAS # 7440-48-4): 231-158-0

Copper (CAS # 7440-50-8): 231-159-6

Vanadium (CAS # 7440-62-2): 231-171-1

Zinc (CAS # 7440-66-6): 231-175-3

Hydrofluoric Acid (CAS # 7664-39-3): 231-634-8

Nitric Acid (CAS # 7697-37-2): 231-714-2

Water (CAS # 7732-18-5): 231-791-2

Selenium (CAS # 7782-49-2): 231-957-4

Aluminum Nitrate Nonahydrate (CAS # 7784-27-2): 236-751-8

Chromium Nitrate Nonahydrate (CAS # 7789-02-8): 236-921-1

Product Number: RSPIKE1 Page 33 of 35



### **SECTION 16: Other Information**

### 16.1. Full Text of Hazard Statements and Precautionary Statements

May be corrosive to metals. Causes severe skin burns and eye damage. Fatal if inhaled. Toxic to aquatic life with long lasting effects.

Keep only in original container. Do not breathe fumes, mist, vapors, or spray. Wash arms, hands and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves and eye protection. In case of inadequate ventilation wear respiratory protection.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. Specific treatment is urgent (Wash areas of contact with water.). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Collect spillage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.

Dispose of contents in accordance with local, state, federal and international regulations.

#### 16.2. Miscellaneous Hazard Classes

Canadian Carcinogenicity Hazard Class: Not Applicable.

Physical Hazards Not Otherwise Classified (PHNOC): Not Applicable.


Health Hazards Not Otherwise Classified (HHNOC): Not Applicable.

Biohazardous Infectious Materials Hazard Class: Not Applicable.

#### 16.3. National Fire Protection Association (NFPA) Rating

Health: 2 Flammability: 0 Reactivity: 0

Special Hazard:



#### 16.4. Document Revision

Last Revision Date: 2023-09-11

Product Number: RSPIKE1 Page 34 of 35

## **DISCLAIMER**

When handled properly by qualified personnel, the product described herein does not present a significant health or safety hazard. Alteration of its characteristics by concentration, evaporation, addition of other substances, or other means may present hazards not specifically addressed herein and which must be evaluated by the user. The information furnished herein is believed to be accurate and represents the best data currently available to us. No warranty, expressed or implied, is made and RICCA CHEMICAL COMPANY assumes no legal responsibility or liability whatsoever resulting from its use.

Product Number: RSPIKE1 Page 35 of 35