Arlington, TX 76012
Pocomoke City, MD 21851
Batesville, IN 47006
http://www.riccachemical.com
1-888-GO-RICCA
customerservice@riccachemical.com

Product Specification

Ionic Strength Adjustor, pH Indicating and Adjusting, for use with Ammonia Selective Electrode

Lot Number: SAMPLE Product Number: 4128

Manufacture Date: N/A
Expiration Date: N/A

Typically, immerse electrode and with stirring then add 2 mL of this solution to 100 mL of each Ammonia Sample and Standard. If each sample solution does not turn and remain Blue after this addition, add additional 1 mL amounts of this product until a Blue color remains, indicating the correct pH range for the Ammonia Selective Electrode Method has been attained. Add the same additional amount, if any, to all of the standards. All lots of this product are tested and certified suitable for use in tests for Ammonia, Ammonia Nitrogen, or Ammonium Ion when using an appropriate Ammonia Selective Electrode Test Method.

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Sodium Hydroxide	1310-73-2	Reagent
Methyl Alcohol	67-56-1	ACS
Ethylenediaminetetraacetic Acid (EDTA), Disodium Salt, Dihydrate	6381-92-6	ACS
Thymolphthalein	125-20-2	ACS

Test	Specification	Result
Ammonia (NH ₃)	To Pass Test	N/A
Appearance	Dark blue liquid	N/A

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
4128-16	500 mL natural poly	24 months
4128-32	1 L natural poly	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

This document is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.

Version: 1.3 Lot Number: SAMPLE Product Number: 4128 Page 1 of 1