

Certificate of Analysis

Sodium Hydroxide, 10.0 Normal

Lot Number: 2308G33 Product Number: 7470			Manufacture Date: AUG 03, 202 Expiration Date: JUL 202	
Name	CAS#	Grade		
Water	7732-18-5	ACS/AS	ГМ/USP/EP	
Sodium Hydroxide	1310-73-2	Reagent		
Test	Specification		Result	NIST SRM#
Appearance	Colorless liquid		Passed	
Assay (vs. Sulfuric Acid/Phenolphthalein)	9.95-10.05 N at 20°C	2	10.05 N at 20°C	723
Heavy Metals (as Pb)	max 10 ppm		10 ppm	
Iron (Fe)	max 5 ppm		5 ppm	3126
Specification	Reference			
Sodium hydroxide Solution (400 g/L)	ASTM (D 3590 A)			
Sodium Hydroxide Solution (400 g/L)	ASTM (D 1426 B)			
Sodium Hydroxide, 10 N	APHA (4500-NH3 D)			
Sodium Hydroxide, 10 N	APHA (4500-CN- L)			
Sodium Hydroxide Stock Solution	APHA (4500-NO3- H)			
Sodium Hydroxide, 10 N	APHA (7500-Ra D)			
ISA Solution (10 M NaOH)	EPA (SW-846) (9213)			
Sodium Hydroxide Solution (10 N)	EPA (SW-846) (3510C)			
Sodium Hydroxide Solution (10 N)	EPA (SW-846) (3520C)			
Sodium Hydroxide (10 N)	EPA (SW-846) (3650B)			
Sodium Hydroxide Solution (10 N)	EPA (SW-846) (3535)			
Sodium Hydroxide Solution (10 Molar)	EPA (SW-846) (3542)			
Sodium Hydroxide, 10 N	EPA (350.3)			
Sodium Hydroxide, 10 N	EPA (351.4)			
Sodium Hydroxide Stock Solution (10 N)	EPA (353.1)			
Sodium Hydroxide, 10 N	E	PA (110.1)		

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
7470-2.5	10 L Cubitainer®	24 months
7470-32	1 L natural poly	24 months
7470-5	20 L Cubitainer®	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

poron Travers.

Sharon Travers (08/03/2023) Operations Manager This document is designed to comply with ISO Guide 31 "Reference Materials --Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.