

Certificate of Analysis

Boric Acid, 2% (w/v)

	le /ASTM/USP/EP	
	/ASTM/USP/EP	
F 9 A A A A		
5-3 ACS		
fication	Result	NIST SRM#
less liquid	Passed	
2.06 % (w/v)	2.02 % (w/v)	84
Reference		
ASTM (D 3590 A)		
APHA (4500-Norg C)		
APHA (4500-NH3 B)		
EPA (SW-846) (9080)		
EPA (350.2)		
EPA (351 3)	
ASTM (D 1426 X1)		
	ASTM (D 2 APHA (450 APHA (450 EPA (SW-8 EPA (350.2 EPA (351.3 ASTM (D ASTM E 288 and NIST Circu	less liquid Passed 2.06 % (w/v) 2.02 % (w/v)

recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part N	umber	Size / Package Type	Shelf Life (Unopened Container)
1065-3	2	 1 L natural poly	24 months
1065-8		 250 mL natural poly	24 months
ъ	1 1 0		

Recommended Storage: 15°C - 30°C (59°F - 86°F)

You Drandon

Paul Brandon (03/22/2024) Production Manager This document is designed to comply with ISO Guide 31 "Reference Materials --Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.