

Certificate of Analysis

Calmagite Indicator, 0.1% (w/v)

Lot Number: 4404C62	Product Number: 1830	Manufacture Date: APR 02, 2024 Expiration Date: MAR 2025
Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Calmagite	3147-14-6	Indicator
Test	Specification	Result
Appearance	Red liquid	Passed
Suitability for Use	Wine Red (Excess Blue (Excess EDT	Ca/Mg) - Pure Passed A)
	Reference	
Specification		Reference
-		Reference APHA (2340 C)
Calmagite Volumetric glassware complies with recalibrated regularly in accordance traceable to the NIST national mass thermometer traceable to NIST stand	with ASTM E 542 and NIST Procedure NBSIR 74 standard. Thermometers and temperature probes	APHA (2340 C) d NIST Circular 434: it is calibrated before first use and 461. Balances are calibrated regularly with weights certified are calibrated before first use and recalibrated regularly with a cer documents that assure manufacture according to validated
Calmagite Volumetric glassware complies with recalibrated regularly in accordance traceable to the NIST national mass thermometer traceable to NIST stand	with ASTM E 542 and NIST Procedure NBSIR 74 standard. Thermometers and temperature probes dards. All products are prepared according to mast	APHA (2340 C) d NIST Circular 434: it is calibrated before first use and 461. Balances are calibrated regularly with weights certified are calibrated before first use and recalibrated regularly with a cer documents that assure manufacture according to validated
Calmagite Volumetric glassware complies with recalibrated regularly in accordance traceable to the NIST national mass thermometer traceable to NIST stand methods. Batch records document ray	with ASTM E 542 and NIST Procedure NBSIR 74 standard. Thermometers and temperature probes dards. All products are prepared according to mast w material traceability and production and testing	APHA (2340 C) d NIST Circular 434; it is calibrated before first use and 461. Balances are calibrated regularly with weights certified are calibrated before first use and recalibrated regularly with a ter documents that assure manufacture according to validated thistory for each lot manufactured.

Recommended Storage: $15^{\circ}C - 30^{\circ}C (59^{\circ}F - 86^{\circ}F)$

You Drandon

Paul Brandon (04/02/2024) Production Manager This document is designed to comply with ISO Guide 31 "Reference Materials --Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.