

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS)

SECTION 1: Identification

1.1. Product Identifier

Trade Name or Designation: ER Wash Solution

Product Number: 2915

Other Identifying Product Numbers: 2915-1

1.2. Recommended Use and Restrictions on Use

General Laboratory Reagent

1.3. Details of the Supplier of the Safety Data Sheet

Company: Ricca Chemical Company

Address: 448 West Fork Drive

Arlington, TX 76012 USA

Telephone: 888-467-4222

1.4. Emergency Telephone Number (24 hours)

CHEMTREC (USA) 800-424-9300

CHEMTREC (International) 1+ 703-527-3887

SECTION 2: Hazard(s) Identification

2.1. Classification of the Substance or Mixture

For the full text of the Hazard and Precautionary Statements listed below, see Section 16.

Hazard Class	Category	Hazard Statements:	Precautionary Statements:
Eye Damage / Irritation	Category 2	H319	P264, P280, P305+P351+P338, P337+P313
Flammable Liquids	Category 2	H225	P210, P233, P240, P241, P242, P243, P280, P303+P361+P353, P370+P378, P403+P235, P501

Safety Data Sheet

2.2. GHS Label Elements

Pictograms:



Signal Word: **Danger**

Hazard Statements:

Hazard Number	Hazard Statement
H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.

Precautionary Statements:

Precautionary Number	Precautionary Statement
P210	Keep away from heat, sparks and open flame. No smoking.
P233	Keep container tightly closed.
P240	Ground container and receiving equipment.
P241	Use explosion-proof equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash arms, hands and face thoroughly after handling.
P280	Wear protective gloves and eye protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical attention.
P370+P378	In case of fire: Use dry chemical, foam or carbon dioxide to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents in accordance with local, state, federal and international regulations.

2.4. Hazards not Otherwise Classified or Covered by GHS

Data not available.

Safety Data Sheet

SECTION 3: Composition / Information on Ingredients

3.1. Components of Substance or Mixture

Chemical Name	Formula	Molecular Weight	CAS Number	Weight%
Acetone	(CH ₃) ₂ CO	58.07 g/mol	67-64-1	74.78
Water	H ₂ O	18.01 g/mol	7732-18-5	24.08
Ethyl Alcohol	CH ₃ CH ₂ OH	46.06 g/mol	64-17-5	1.09
Methyl Alcohol	CH ₃ OH	32.04 g/mol	67-56-1	< 0.1

SECTION 4: First-Aid Measures

4.1. General First Aid Information

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. May cause irritation with burning and stinging with possible damage to the cornea and conjunctiva.

Inhalation: Not expected to require first aid. If necessary, remove to fresh air.

Skin Contact: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Results in drying and cracking which can lead to secondary infections and dermatitis.

Ingestion: Aspiration hazard. Do not induce vomiting, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Call a physician.

4.2. Most Important Symptoms and Effects, Acute and Delayed

Causes serious eye irritation. Flammable liquid. Primarily toxic by ingestion. If ingested, give large quantity of water. Vomiting may occur spontaneously, do not induce. Call a physician. Contact may cause dryness and cracking of the skin. May cause irritation to the eyes. Wash areas of contact with plenty of water. May cause irritation of the respiratory system. EYE CONTACT: May cause irritation with burning and stinging with possible damage to the cornea and conjunctiva. SKIN CONTACT: Results in drying and cracking which can lead to secondary infections and dermatitis.

4.3. Medical Attention or Special Treatment Needed

Irrigate immediately with large quantity of water for at least 15 minutes. Call a physician if irritation develops. Remove to fresh air. Give artificial respiration if necessary. If breathing is difficult, give oxygen. Wash areas of contact with soap and water for at least 15 minutes. Call a physician if irritation develops. Aspiration hazard. Do not induce vomiting, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Call a physician.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing Media

In case of fire: Use dry chemical, foam or carbon dioxide to extinguish. Dry chemical, alcohol foam, carbon dioxide



Safety Data Sheet

5.2. Specific Hazards Arising from the Substance or Mixture

Highly flammable liquid and vapor. Vapors can flow along surfaces to distant ignition source and flashback. Use water spray to blanket fire, cool fire exposed containers, and to flush non-ignited spills or vapors away from fire. Explosion hazard when exposed to heat, flame or oxidizers.

5.3. Special Protective Equipment for Firefighters

Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Ground container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye protection.

6.2. Cleanup and Containment Methods and Materials

Remove all sources of ignition. Contain spill. Do not flush to sewer. Absorb with suitable inert material (vermiculite, dry sand, etc) and place in a chemical waste container for proper disposal in an approved waste disposal facility. Ventilate area of spill. Have extinguishing agent available in case of fire. Use non-sparking tools and equipment. Dispose of in accordance with local regulations.

SECTION 7: Handling and Storage

7.1. Precautions for Safe Handling and Storage Conditions

Store in a well-ventilated place. Keep cool. As with all chemicals, wash hands thoroughly after handling. Avoid contact with eyes and skin. Protect from freezing and physical damage. Store in secure, flammable storage area away from all sources of ignition. Empty containers may be hazardous since they retain product residues.

Safety Data Sheet

SECTION 8: Exposure Controls / Personal Protection

8.1 Control Parameters

Chemical Name	Limit Type	Country	Exposure Limit	Information Source
Ethyl Alcohol (64-17-5)	TWA	USA	"1000 ppm TWA; 1900 mg/m ³ TWA" As Ethyl alcohol [64-17-5]	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Ethyl Alcohol (64-17-5)	TLV-STEL	USA	"1000 ppm STEL" As Ethanol [64-17-5]	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Ethyl Alcohol (64-17-5)	TWA	USA	1000 ppm TWA; 1900 mg/m ³ TWA	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Ethyl Alcohol (64-17-5)	TLV-STEL	USA	1000 ppm STEL	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Ethyl Alcohol (64-17-5)	TLV-STEL	USA	"1000 ppm STEL" As Ethanol [64-17-5]	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Ethyl Alcohol (64-17-5)	TWA	USA	"1000 ppm TWA; 1900 mg/m ³ TWA" As Ethyl alcohol [64-17-5]	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Ethyl Alcohol (64-17-5)	TLV-STEL	USA	"1000 ppm STEL" As Ethanol [64-17-5]	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Ethyl Alcohol (64-17-5)	TWA	USA	"1000 ppm TWA; 1900 mg/m ³ TWA" As Ethyl alcohol [64-17-5]	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Ethyl Alcohol (64-17-5)	TLV-STEL	USA	"1000 ppm STEL" As Ethanol [64-17-5]	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Ethyl Alcohol (64-17-5)	TWA	USA	"1000 ppm TWA; 1900 mg/m ³ TWA" As Ethyl alcohol [64-17-5]	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Methyl Alcohol (67-56-1)	TLV-STEL	USA	"250 ppm STEL" As Methanol [67-56-1]	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Methyl Alcohol (67-56-1)	TWA	USA	"200 ppm TWA; 260 mg/m ³ TWA" As Methyl alcohol [67-56-1]	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Methyl Alcohol (67-56-1)	TLV-TWA	USA	"200 ppm TWA" As Methanol [67-56-1]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Methyl Alcohol (67-56-1)	TWA	USA	"200 ppm TWA; 260 mg/m ³ TWA" As Methyl alcohol [67-56-1]	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)

Safety Data Sheet

Methyl Alcohol (67-56-1)	TLV-TWA	USA	"200 ppm TWA" As Methanol [67-56-1]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Methyl Alcohol (67-56-1)	TLV-STEL	USA	"250 ppm STEL" As Methanol [67-56-1]	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Methyl Alcohol (67-56-1)	TWA	USA	200 ppm TWA; 260 mg/m ³ TWA	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Methyl Alcohol (67-56-1)	TLV-TWA	USA	200 ppm TWA	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Methyl Alcohol (67-56-1)	TLV-STEL	USA	250 ppm STEL	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Methyl Alcohol (67-56-1)	TLV-TWA	USA	"200 ppm TWA" As Methanol [67-56-1]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Methyl Alcohol (67-56-1)	TLV-STEL	USA	"250 ppm STEL" As Methanol [67-56-1]	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Methyl Alcohol (67-56-1)	TWA	USA	"200 ppm TWA; 260 mg/m ³ TWA" As Methyl alcohol [67-56-1]	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Acetone (67-64-1)	TWA	USA	1000 ppm TWA; 2400 mg/m ³ TWA	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Acetone (67-64-1)	TLV-TWA	USA	250 ppm TWA	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Acetone (67-64-1)	TLV-STEL	USA	500 ppm STEL	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Acetone (67-64-1)	TLV-STEL	USA	"500 ppm STEL" As Acetone [67-64-1]	ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)
Acetone (67-64-1)	TLV-TWA	USA	"250 ppm TWA" As Acetone [67-64-1]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Acetone (67-64-1)	TWA	USA	"1000 ppm TWA; 2400 mg/m ³ TWA" As Acetone [67-64-1]	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)

8.2. Exposure Controls

Engineering Controls: A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limit.

Respiratory Protection: If the TLV is exceeded, a half-mask organic vapor respirator may be worn for up to 10 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full facepiece organic vapor respirator may be worn for up to 50 times the exposure limit, or the maximum use concentration specified by the respirator supplier, whichever is lowest.

Skin Protection: Wear protective gloves and eye protection. Chemical resistant gloves.

Eye Protection: Wear protective gloves and eye protection. Safety glasses or goggles.



Safety Data Sheet

8.3. Personal Protective Equipment

Wear protective gloves and eye protection. If the TLV is exceeded, a half-mask organic vapor respirator may be worn for up to 10 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full facepiece organic vapor respirator may be worn for up to 50 times the exposure limit, or the maximum use concentration specified by the respirator supplier, whichever is lowest. Chemical resistant gloves. Safety glasses or goggles.

SECTION 9: Physical and Chemical Properties

9.1. Basic Physical and Chemical Properties

Appearance: Colorless liquid

Physical State: Liquid

Odor: Data not available.

Odor Threshold: Data not available.

pH: Data not available.

Melting/Freezing Point: Data not available.

Initial Boiling Point/Range: Approximately 60°C - Approximately 60°C

Flash Point: Approximately -5°C

Evaporation Rate: Data not available.

Flammability: Data not available.

Flammability/Explosive Limits: Data not available.

Vapor Pressure: Data not available.

Vapor Density: Data not available.

Relative Density: 0.85

Solubility: Miscible

Partition Coefficient: Data not available.

Auto-Ignition Temperature: Data not available.

Decomposition Temperature: Data not available.

Viscosity: Data not available.

Explosive Properties: Data not available.

Oxidizing Properties: Data not available.

SECTION 10: Stability and Reactivity

10.1. Reactivity and Chemical Stability

Stable under normal conditions of use and storage.

Safety Data Sheet

10.2. Possibility of Hazardous Reactions

Data not available.

10.3. Conditions to Avoid and Incompatible Materials

Keep away from heat, sparks and open flame. No smoking. Keep container tightly closed. Oxidizers, Nitric-Sulfuric Acid Mixtures, Acids, Chromium Trioxide, Sulfuric Acid-Potassium Dichromate, Hydrogen Peroxide, heat, sparks, open flame.

10.4. Hazardous Decomposition Products

Will not occur.

SECTION 11: Toxicological Information

11.1. Information on Toxicological Effects

Acute Toxicity - Oral Exposure:

Not applicable.

Acute Toxicity - Dermal Exposure:

Not applicable.

Acute Toxicity - Inhalation Exposure:

Not applicable.

Acute Toxicity - Other Information:

LD50, Oral, Rat: (Acetone) 5800 mg/kg, behavioral effects noted; (Methanol) 5628 mg/kg, Details of toxic effects not reported other than lethal dose value; (Ethanol) 7060 mg/kg, respiration changes noted.

Skin Corrosion and Irritation:

Not applicable.

Serious Eye Damage and Irritation:

Causes serious eye irritation. Wash arms, hands and face thoroughly after handling. Wear protective gloves and eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Respiratory Sensitization:

Not applicable.

Skin Sensitization:

Not applicable.

Germ Cell Mutagenicity:

Not applicable.

Carcinogenicity:

Not applicable.

Reproductive Toxicity:

Not applicable.

Specific Target Organ Toxicity from Single Exposure:

Not applicable.



Safety Data Sheet

Specific Target Organ Toxicity from Repeated Exposure:

Not applicable.

Aspiration Hazard:

Not applicable.

Additional Toxicology Information:

Data not available.

SECTION 12: Ecological Information

12.1. Ecotoxicity

Not applicable.

12.2. Persistence and Degradability

Data not available.

12.3. Bioaccumulative Potential

Data not available.

12.4. Mobility in Soil

Data not available.

12.5. Other Adverse Ecological Effects

Data not available.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Data not available.



Safety Data Sheet

SECTION 14: Transportation Information

14.1. Transportation by Land-Department of Transportation (DOT, United States of America)

Sizes: 4 L

UN Number: UN1993

Proper Shipping Name: Flammable Liquid, n.o.s. (Acetone, Ethanol)

Hazard Class: 3

Packing Group: II

Hazard Label(s):



14.2. Transportation by Air - International Air Transport Association (IATA)

Sizes: 4 L

UN Number: UN1993

Proper Shipping Name: Flammable Liquid, n.o.s. (Acetone, Ethanol)

Hazard Class: 3

Packing Group: II

Hazard Label(s):



14.3 Transportation of Dangerous Goods (TDG, Canada)

Sizes: 4 L

UN Number: UN1993

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (acetone, ethanol)

Hazard Class: 3

Packing Group: II

Hazard Label(s):



Safety Data Sheet

SECTION 15: Regulatory Information

15.1. Occupational Safety and Health Administration (OSHA) Hazards

Not listed.

15.2. Superfund Amendments and Reauthorization Act (SARA) 302 Extremely Hazardous Substances

Not listed.

15.3. Superfund Amendments and Reauthorization Act (SARA) 311/312 Hazardous Chemicals

Methyl Alcohol (CAS # 67-56-1): "5000 lb final RQ; 2270 kg final RQ" As Methanol [67-56-1]

Methyl Alcohol (CAS # 67-56-1): 5000 lb final RQ; 2270 kg final RQ

Acetone (CAS # 67-64-1): "5000 lb final RQ; 2270 kg final RQ" As Acetone [67-64-1]

Acetone (CAS # 67-64-1): 5000 lb final RQ; 2270 kg final RQ

15.4. Superfund Amendments and Reauthorization Act (SARA) 313 Toxic Release Inventory (TRI)

Methyl Alcohol (CAS # 67-56-1): "1.0 % de minimis concentration" As Methanol [67-56-1]

Methyl Alcohol (CAS # 67-56-1): 1.0 % de minimis concentration

15.5. Massachusetts Right-to-Know Substance List

Ethyl Alcohol (CAS # 64-17-5): "Teratogen" As Ethyl alcohol [64-17-5]

Ethyl Alcohol (CAS # 64-17-5): Teratogen

Methyl Alcohol (CAS # 67-56-1): "Present" As Methanol [67-56-1]

Methyl Alcohol (CAS # 67-56-1): Present

Acetone (CAS # 67-64-1): "Present" As Acetone [67-64-1]

Acetone (CAS # 67-64-1): Present

15.6. Pennsylvania Right-to-Know Hazardous Substances

Ethyl Alcohol (CAS # 64-17-5): "Present" As Denatured alcohols [RR-00113-8]

Ethyl Alcohol (CAS # 64-17-5): "Present" As Ethanol [64-17-5]

Ethyl Alcohol (CAS # 64-17-5): Present

Methyl Alcohol (CAS # 67-56-1): "Environmental hazard" As Methanol [67-56-1]

Methyl Alcohol (CAS # 67-56-1): "Present" As Denatured alcohols [RR-00113-8]

Methyl Alcohol (CAS # 67-56-1): "Present" As Methanol [67-56-1]

Methyl Alcohol (CAS # 67-56-1): Environmental hazard

Methyl Alcohol (CAS # 67-56-1): Present

Acetone (CAS # 67-64-1): "Environmental hazard" As 2-Propanone [67-64-1]

Acetone (CAS # 67-64-1): "Present" As 2-Propanone [67-64-1]

Acetone (CAS # 67-64-1): Environmental hazard

Acetone (CAS # 67-64-1): Present

Water (CAS # 7732-18-5): "Present" As Ethyl alcohol and water [RR-00802-6]

Water (CAS # 7732-18-5): Present

Safety Data Sheet

15.7. New Jersey Worker and Community Right-to-Know Components

Ethyl Alcohol (CAS # 64-17-5): "carcinogen; flammable - third degree; mutagen; teratogen" As Ethyl alcohol [64-17-5]
Ethyl Alcohol (CAS # 64-17-5): "sn 0844" As Ethyl alcohol [64-17-5]
Ethyl Alcohol (CAS # 64-17-5): carcinogen; flammable - third degree; mutagen; teratogen
Ethyl Alcohol (CAS # 64-17-5): sn 0844
Methyl Alcohol (CAS # 67-56-1): "flammable - third degree; teratogen" As Methyl alcohol [67-56-1]
Methyl Alcohol (CAS # 67-56-1): "SN 1222 500 lb TPQ" As Methanol [67-56-1]
Methyl Alcohol (CAS # 67-56-1): "sn 1222" As Methyl alcohol [67-56-1]
Methyl Alcohol (CAS # 67-56-1): flammable - third degree; teratogen
Methyl Alcohol (CAS # 67-56-1): sn 1222
Methyl Alcohol (CAS # 67-56-1): SN 1222 500 lb TPQ
Acetone (CAS # 67-64-1): "flammable - third degree" As Acetone [67-64-1]
Acetone (CAS # 67-64-1): "sn 0006" As Acetone [67-64-1]
Acetone (CAS # 67-64-1): flammable - third degree
Acetone (CAS # 67-64-1): sn 0006

15.8. California Proposition 65

Ethyl Alcohol (CAS # 64-17-5): "carcinogen, 7/1/1988 (when associated with alcohol abuse); carcinogen, 4/29/2011" As Alcoholic beverages [RR-01961-4]
Ethyl Alcohol (CAS # 64-17-5): "developmental toxicity, 10/1/1987 (listed under Ethyl alcohol in alcoholic beverages)" As Alcoholic beverages [RR-01961-4]
Ethyl Alcohol (CAS # 64-17-5): carcinogen, 7/1/1988 (when associated with alcohol abuse); carcinogen, 4/29/2011
Ethyl Alcohol (CAS # 64-17-5): developmental toxicity, 10/1/1987 (listed under Ethyl alcohol in alcoholic beverages)
Methyl Alcohol (CAS # 67-56-1): "developmental toxicity, 3/16/2012" As Methanol [67-56-1]
Methyl Alcohol (CAS # 67-56-1): developmental toxicity, 3/16/2012

15.9. Canada Domestic Substances List / Non-Domestic Substances List (DSL/NDSL)

Ethyl Alcohol (CAS # 64-17-5): "Present" As Alcohols, C1-3 [68475-56-9] (NDSL)
Ethyl Alcohol (CAS # 64-17-5): "Present" As Ethyl alcohol [64-17-5] (DSL)
Ethyl Alcohol (CAS # 64-17-5): Present (DSL)
Ethyl Alcohol (CAS # 64-17-5): Present (NDSL)
Methyl Alcohol (CAS # 67-56-1): "Present" As Alcohols, C1-3 [68475-56-9] (NDSL)
Methyl Alcohol (CAS # 67-56-1): "Present" As Methyl alcohol [67-56-1] (DSL)
Methyl Alcohol (CAS # 67-56-1): Present (DSL)
Methyl Alcohol (CAS # 67-56-1): Present (NDSL)
Acetone (CAS # 67-64-1): "Present" As Acetone [67-64-1] (DSL)
Acetone (CAS # 67-64-1): Present (DSL)
Water (CAS # 7732-18-5): "Present" As Water [7732-18-5] (DSL)
Water (CAS # 7732-18-5): Present (DSL)

Safety Data Sheet

15.10. United States of America Toxic Substances Control Act (TSCA) List

All components of this solution are listed as active on the TSCA Inventory or are mixtures (hydrates) of active items listed on the TSCA Inventory.

Ethyl Alcohol (CAS # 64-17-5): "Present (ACTIVE)" As Ethanol [64-17-5]

Ethyl Alcohol (CAS # 64-17-5): Present (ACTIVE)

Methyl Alcohol (CAS # 67-56-1): "Present (ACTIVE)" As Methanol [67-56-1]

Methyl Alcohol (CAS # 67-56-1): Present (ACTIVE)

Acetone (CAS # 67-64-1): "Present (ACTIVE)" As 2-Propanone [67-64-1]

Acetone (CAS # 67-64-1): Present (ACTIVE)

Water (CAS # 7732-18-5): "Present (ACTIVE)" As Water [7732-18-5]

Water (CAS # 7732-18-5): Present (ACTIVE)

15.11. European Inventory of Existing Commercial Chemical Substances (EINECS), European List of Notified Chemical Substances (ELINCS), and No Longer Polymers (NLP)

Ethyl Alcohol (CAS # 64-17-5): "200-578-6" As Ethanol [64-17-5]

Ethyl Alcohol (CAS # 64-17-5): 200-578-6

Ethyl Alcohol (CAS # 64-17-5): 270-649-4

Methyl Alcohol (CAS # 67-56-1): "200-659-6" As Methanol [67-56-1]

Methyl Alcohol (CAS # 67-56-1): 200-659-6

Methyl Alcohol (CAS # 67-56-1): 270-649-4

Acetone (CAS # 67-64-1): "200-662-2" As Acetone [67-64-1]

Acetone (CAS # 67-64-1): 200-662-2

Water (CAS # 7732-18-5): "231-791-2" As Water [7732-18-5]

Water (CAS # 7732-18-5): 231-791-2

SECTION 16: Other Information

16.1. Full Text of Hazard Statements and Precautionary Statements

Highly flammable liquid and vapor. Causes serious eye irritation.

Keep away from heat, sparks and open flame. No smoking. Keep container tightly closed. Ground container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash arms, hands and face thoroughly after handling. Wear protective gloves and eye protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire: Use dry chemical, foam or carbon dioxide to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents in accordance with local, state, federal and international regulations.

Safety Data Sheet

16.2. Miscellaneous Hazard Classes

Canadian Carcinogenicity Hazard Class: Not Applicable.


Physical Hazards Not Otherwise Classified (PHNOC): Not Applicable.

Health Hazards Not Otherwise Classified (HHNOC): Not Applicable.

Biohazardous Infectious Materials Hazard Class: Not Applicable.

16.3. National Fire Protection Association (NFPA) Rating

Health: 1
Flammability: 3
Reactivity: 0
Special Hazard:



16.4. Document Revision

Last Revision Date: 2025-01-30

DISCLAIMER

When handled properly by qualified personnel, the product described herein does not present a significant health or safety hazard. Alteration of its characteristics by concentration, evaporation, addition of other substances, or other means may present hazards not specifically addressed herein and which must be evaluated by the user. The information furnished herein is believed to be accurate and represents the best data currently available to us. No warranty, expressed or implied, is made and RICCA CHEMICAL COMPANY assumes no legal responsibility or liability whatsoever resulting from its use.