

## **Product Specification**

## Hydrofluoric Acid, 0.5% (v/v)

Lot Number: SAMPLE

## Manufacture Date: N/A

Expiration Date: N/A

Name	CAS#	Grade	
Water	7732-18-5	ACS/ASTM/USP/EP	
Hydrofluoric Acid	7664-39-3	ACS	
	a	<b>D</b> 1	NITOT ODM#

Product Number: R3815500

Te	st	Specification	$\operatorname{Result}$	NIST SRM#
Ap	pearance	Colorless liquid	N/A	
As	say (vs. Sodium Hydroxide/Phenolphthalein)	0.48-0.52 % (v/v)	N/A	84

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
R3815500-1A	1 L natural poly	24 months
R3815500-20F	20 L Cubitainer®	24 months
R3815500-250A	250 mL natural poly	24 months
R3815500-4A	4 L natural poly	24 months
R3815500-500A	500 mL natural poly	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

This document is designed to comply with ISO Guide 31 "Reference Materials --Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.