

Product Specification

Potassium Permanganate Standard, 891 mg/L (1000 ppm as Cl₂)

Lot Number: SAMPLE**Product Number:** R6354300**Manufacture Date:** N/A**Expiration Date:** N/A

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Potassium Permanganate	7722-64-7	ACS

Test	Specification	Result	NIST SRM#
Appearance	Purple liquid	N/A	
Assay (vs. Sodium Oxalate)	0.02815-0.02825 N at 20°C	N/A	8040

Specification	Reference
Potassium Permanganate stock	APHA (4500-Cl G)
Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.	

Part Number	Size / Package Type	Shelf Life (Unopened Container)
R6354300-1C	1 L amber glass	18 months
R6354300-500C	500 mL amber glass	18 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

This document is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.