Arlington, TX 76012
Pocomoke City, MD 21851
Batesville, IN 47006
http://www.riccachemical.com
1-888-GO-RICCA
customerservice@riccachemical.com

Product Specification

Sodium Nitrate, 5.0 Molar, Ionic Strength Adjustor

Lot Number: SAMPLE Product Number: 7496

Manufacture Date: N/A Expiration Date: N/A

Suitable for use as an Ionic Strength Adjustor (ISA) for concentration measurement of Bromide (Br), Cadmium (Cd²), Chloride (Cl), Cupric (Cu²), Iodide (I), Silver (Ag¹), and Thiocyanate (SCN) in various Ion Selective Electrode (ISE) Methods.

| Name | CAS# | Grade | |
|----------------|-----------|-----------------|--|
| Water | 7732-18-5 | ACS/ASTM/USP/EP | |
| Sodium Nitrate | 7631-99-4 | ACS | |

| Test | Specification | Result | |
|-----------------------------|------------------|--------|--|
| Appearance | Colorless liquid | N/A | |
| Assay (by Refractive Index) | 4.93-5.07 Molar | N/A | |

| Specification | Reference |
|--------------------------|---------------------|
| Ionic Strength Adjuster | ASTM (D 3869 C) |
| ISA Solution (5 M NaNO3) | EPA (SW-846) (9211) |
| ISA Solution (5 M NaNO3) | EPA (SW-846) (9212) |
| Ionic Strength Adjustor | ASTM (D 1246) |

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

| Part Number | Size / Package Type | Shelf Life (Unopened Container) |
|-------------|---------------------|---------------------------------|
| 7496-1 | 4 L natural poly | 24 months |
| 7496-16 | 500 mL natural poly | 24 months |
| 7496-32 | 1 L natural poly | 24 months |

Recommended Storage: 15°C - 30°C (59°F - 86°F)

This document is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.

Version: 1.3 Lot Number: SAMPLE Product Number: 7496 Page 1 of 1