

# Certificate of Analysis

**Potassium Permanganate, 0.0500 Normal (N/20), 0.0100 Molar (M/100)**

**Lot Number:** 2402F83

**Product Number:** 6390

**Manufacture Date:** FEB 21, 2024

**Expiration Date:** AUG 2025

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Potassium Permanganate	7722-64-7	ACS

Test	Specification	Result	NIST SRM#
Appearance	Purple liquid	Passed	
Assay (vs. Sodium Oxalate)	0.04995-0.05005 N at 20°C	0.05002 N at 20°C	8040

Specification	Reference
Potassium permanganate, 0.05 N	TAPPI (T 618 cm-84)
Standard Potassium Permanganate Titrant	APHA (4500-NO2- B)
Standard Potassium Permanganate Titrant, 0.01 M	APHA (3500-Ca B)
Potassium permanganate, 0.05 N	TAPPI (T 430 om-94)

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
6390-32	1 L amber glass	18 months

**Recommended Storage:** 15°C - 30°C (59°F - 86°F)



Jose Pena (02/21/2024)

Operations Manager

This document is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.