## RICCA CHEMICAL COMPANY®

## **Certificate of Analysis**

## Sodium Hydroxide, 10% (w/v) (100 g/L)

Lot Number: 2402H55 Product N	Number: 7260	Manufacture Date: FEB 28, 2024 Expiration Date: FEB 2027	
Name	CAS#	Grade	
Water	7732-18-5	ACS/ASTM/USP/EP	
Sodium Hydroxide	1310-73-2	Reagent	
Test	Specification	Result	NIST SRM#
Appearance	Colorless liquid	Passed	
Assay (vs. Sulfuric Acid/Phenolphthalein)	9.96-10.04 % (w/v)	10.00 % (w/v)	723
Specification	Re	eference	

Specification	Reference	Reference	
Sodium hydroxide solution (100 g/1000 mL)	TAPPI (T 602 cm-97)		
Sodium Hydroxide Solution (100 g/L)	ASTM (D 3866 A)		
Sodium Hydroxide Solution (100 g/L)	ASTM (D 858 B)		
Sodium Hydroxide Solution (100 g/L)	ASTM (D 1886 B)		
Sodium Hydroxide Solution (100 g/L)	ASTM (D 3557 B)		
Sodium Hydroxide Solution (100 g/L)	ASTM (D 3558 B)		
Sodium Hydroxide Solution (100 g/L)	ASTM (D 1688 B)		
Sodium Hydroxide Solution (100 g/L)	ASTM (D 3559 B)		
Sodium hydroxide, 10% solution	TAPPI (T 618 cm-84)		
Sodium Hydroxide Solution (100 g/L)	ASTM (D 1266)		
Sodium Hydroxide Solution (100 g/L)	ASTM (D 3372)		
Sodium Hydroxide Solution (100 g/L)	ASTM (D 1266)		
Sodium Hydroxide Reagent Solution	ACS (N/A)		

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
7260-1	4 L natural poly	36 months
7260-4	120 mL natural poly	36 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

Ø

Jose Pena (02/28/2024) Operations Manager This document is designed to comply with ISO Guide 31 "Reference Materials --Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.