

Manufacture Date: FFB 20 2024

## **Certificate of Analysis**

## Nitric Acid, 10% (v/v)

Nitric Acid (1+9)

Nitric Acid (1+9)

Lot Number: 4402L04	Product Number: $5320$			n Date: FEB 20, 202 n Date: FEB 202
Name	CAS#	Grade		
Water	7732-18-5	ACS/AST	M/USP/EP	
Nitric Acid	7697-37-2	ACS		
Test	Specification		Result	NIST SRM#
Appearance	Colorless to light y	vellow liquid	Passed	
Appearance Assay (vs. Sodium Hydroxid		zellow liquid	Passed 10.0 % (v/v)	84
		vellow liquid Reference		
Assay (vs. Sodium Hydroxid			10.0 % (v/v)	84
Assay (vs. Sodium Hydroxid Specification		Reference	10.0 % (v/v) 1)	
Assay (vs. Sodium Hydroxid <b>Specification</b> Nitric Acid		Reference ASTM (D 287 M	10.0 % (v/v) 1) A)	84
Assay (vs. Sodium Hydroxid <b>Specification</b> Nitric Acid Nitric Acid (1+9)		Reference ASTM (D 287 M ASTM (D 2907	10.0 % (v/v) 1) A) C)	84
Assay (vs. Sodium Hydroxid Specification Nitric Acid Nitric Acid (1+9) Nitric Acid (1+9)		Reference ASTM (D 287 M ASTM (D 2907 ASTM (D 2972	10.0 % (v/v) 1) A) C) H)	84
Assay (vs. Sodium Hydroxid Specification Nitric Acid Nitric Acid (1+9) Nitric Acid (1+9) Nitric Acid (1+9)		Reference ASTM (D 287 M ASTM (D 2907 ASTM (D 2972 ASTM (D 2187	10.0 % (v/v) 1) A) C) H)	······
Assay (vs. Sodium Hydroxid Specification Nitric Acid Nitric Acid (1+9) Nitric Acid (1+9) Nitric Acid (1+9) Nitric Acid (1+9) Nitric Acid (1+9)		Reference   ASTM (D 287 N   ASTM (D 2907   ASTM (D 2972   ASTM (D 2187   ASTM (D 2187   ASTM (D 4548)	10.0 % (v/v) 1) A) C) H)	84

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

ASTM (D 2187 K) ASTM (D 2187 L)

Part Number	Size / Package Type	Shelf Life (Unopened Container)		
5320-1	4 L natural poly	24 months		
5320-16	500 mL natural poly	24 months		
5320-32	1 L natural poly	24 months		
5320-5HP	20 L Ropak™	24 months		
<b>B</b> <sub>222</sub> $d_{2}$ $d_{$				

**Recommended Storage**: 15°C - 30°C (59°F - 86°F)

Fand Brandon

Paul Brandon (02/20/2024) Production Manager This document is designed to comply with ISO Guide 31 "Reference Materials --Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.